




ISA-PLAN® // PRECISION RESISTORS



FMP // Size 2010



Features

- Power rating up to 3.5 W at 70°C (2 mOhm)
- Constant current up to 41 A (2 mOhm)
- Standard pad size (2010)
- High pulse power rating
- Excellent long-term stability
- Mounting: Reflow- and IR-soldering/vacuum soldering recommended
- AEC-Q200 qualified
- RoHS 2011/65/EU compliant



Applications

- Current sensor for power hybrid applications
- Control systems for the automotive market
- Power modules
- Frequency converters
- Switch mode power supplies


Technical data

Resistance values	mOhm	2 / 3 / 4 / 5 / 6
Tolerance	%	1 / 5
Temperature coefficient (20-60 °C)	ppm/K	<50
Applicable temperature range	°C	-65 to +170
Power rating	W	up to 3.5
Dielectric withstanding voltage	V AC/DC	200
Inductance	nH	<1
Stability (at rated power) deviation after 2000h, T _K = Terminal temperature		< 0.5 % (TK=80 °C) < 1.0 % (TK=110 °C)

Type	Value [mΩ]	R _{thi} [K/W]	TCR [ppm/K]	P _{70 °C} [W]	P _{110 °C} [W]	Available tolerances	
						1 %	5 %
FMP-M-R002	2	<26	<50	3.5	2	✓	✓
FMP-M-R003	3	<32	<50	2.5	1.5	✓	✓
FMP-V-R004	4	<38	<50	2.5	1	✓	✓
FMP-V-R005	5	<44	<50	2	1	✓	✓
FMP-V-R006	6	<50	<50	2	1	✓	✓

Ordering code

FMP - M - R003 - 1.0






FMP // Size 2010

Recommended solder profile

Reflow- and IR-soldering / vacuum soldering recommended

Temperature	°C	260	255	217
Time	sec	peak	40	90




Tape and reel information

Specification	DIN EN 60286-3		
Tape width	mm	12	
Reel size	inch	13	
Parts per reel	pcs	12500	
Packaging weight net	g	481	

Information

Parts are not marked

Mechanical dimensions and pcb-layout proposal (Reflow-soldering) [mm] / Drawing Z-YL-257a




type:	L	W	H	A
FMP	5.08 ±0.2	2.54 ±0.2	0.4 ±0.1	0.7 ±0.2

solder pad type:	l	w	a
FMP	5.78	2.44	1.25




FMP // Size 2010


Temperature dependence of the electrical resistance of MANGANIN® resistors



Temperature dependence of the electrical resistance of NOVENTIN® resistors



Power derating curve






FMP // Size 2010

Maximum pulse energy respectively pulse power for permanent operation

FMP-M-R002; FMP-V-R004; FMP-V-R006

Maximum pulse energy / power for continuous operation ($T_K=110\text{ °C}$)



Specification

Parameters	Test conditions	Specified values
Temperature Cycling	2000 cycles (-55 °C to +150 °C)	±0.5%
Low Temperature Storage	-65 °C for 250 h	±0.1%
Moisture Resistance	MIL-STD-202 method 106	±0.2%
Mechanical Shock	100 g, 6 ms half sine	±0.1%
Vibration, High Frequency	10 g, 10-2000 Hz, 24 h each axis	±0.1%
Operational Life	2000 h, $T_K=110\text{ °C}$ at rated power	±1.0%
High Temperature Exposure	2000 h at 170 °C	±1.0%
Bias Humidity	+85 °C, 85 r.F., 1000 h, powered	±0.5%

Disclaimer // All products, product specifications and data are subject to change without notice.

The product specifications do not expand or otherwise modify Isabellenhütte's terms and conditions of sale, including but not limited to, the warranty expressed therein. Isabellenhütte makes no warranty, representation or guarantee other than as set forth in its terms and conditions of sale.

Information provided in datasheets and/or specifications may vary from actual results in different applications. Any statements made by Isabellenhütte regarding the suitability of products for certain types of applications are based on its knowledge of typical requirements that are often placed on its products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in the application intended.

No license, express or implied, or otherwise, to any intellectual property rights is granted by this document.

Any and all liability arising out of the application or use of any product shall be as set forth in Isabellenhütte's terms and conditions of sale.