

# Technical Information

The following chapter contains practical information on the behaviour, during and after subsequent treatment, of the alloys delivered by Isabellenhütte. This information is intended to assist in selecting the correct alloy for the appropriate application. As a matter of fact, this information cannot handle all imaginable applications in detail. For special questions, please contact our experts for support. A collection of the most important and most often used conversion tables concludes this chapter.



**ISABELLENHÜTTE**

Innovation by Tradition

# A. The Electrical Resistance and its Temperature Coefficient

## Resistivity

In accordance with the equation

$$R_t = \frac{\rho_t \cdot l}{S}$$

the electrical resistance of a conductor at temperature  $t$  is proportional to its length and inversely proportional to its cross-sectional area on the condition that there is a constant cross-section over the whole test length.

$R_t$  = Resistance in  $\Omega$  at temperature  $T$

$l$  = Length in m

$S$  = Cross-Sectional area in  $\text{mm}^2$

$\rho_t$  = Resistivity in  $\Omega \cdot \text{mm}^2 \cdot \text{m}^{-1}$  at temperature  $T$

In order to calculate

$$\rho_t = R_t \cdot \frac{S}{l}$$

$R_t$ ,  $S$  and  $l$  are determined. If

$$S = 1 \text{ mm}^2 \quad \text{and} \quad l = 1 \text{ m}$$

are given, one calculates the resistivity in  $\Omega \cdot \text{mm}^2 \cdot \text{m}^{-1}$ , i. e. the resistance of a conductor of 1 m length and 1  $\text{mm}^2$  cross-sectional area.

The resistivity can also be defined as to be the electrical resistance of a cube with 1 cm edge length; then it is expressed in units of  $\Omega \cdot \text{cm}$ . Since for base metals and alloys the resistance of such a cube is very low, the resistance values are expressed in  $\mu\Omega \cdot \text{cm}$ , i. e. in millionths of an  $\Omega \cdot \text{cm}$ .

The values for e.g. ISOTAN® would then be either

$$0.49 \Omega \cdot \text{mm}^2 \cdot \text{m}^{-1}$$

or

$$49 \mu\Omega \cdot \text{cm}.$$

The practical determination of the resistivity can be difficult, since determination of the cross-sectional area of e. g. wires with non-circular cross-section or very thin wires is difficult. In such cases, the cross-sectional area is determined on the basis of weight and length.

The resistivity of a wire can then be determined in accordance with the equation:

$$\rho_t = \frac{R_t \cdot g}{\gamma} \cdot \frac{1}{l^2}$$

$R_t$  = Resistance in  $\Omega$  at temperature  $T$

$\rho_t$  = Resistivity in  $\Omega \cdot \text{mm}^2 \cdot \text{m}^{-1}$  at temperature  $T$

$g$  = Weight in g

$\gamma$  = Density in  $\text{g}/\text{cm}^3$

$l$  = Length in m

For countries using a different system of measurement the resistivity is expressed in units which must be converted when changing over

from one system to another (see Annex "Conversion Tables"):

## Resistance per Meter

The resistance per meter of a conductor is determined by the quotient of its resistivity and cross-sectional values.


## The Temperature Coefficient ( $\alpha$ ) of Resistivity

Metals and their alloys exhibit a dependence of the resistivity on temperature. In general the resistivity increases with temperature. In a simplified form the temperature dependence of resistivity can be expressed by the equation:

$$R_t = R_0 \cdot [1 + \alpha (T - T_0)]$$

This equation applies only if resistance and temperature expose a linear relationship in the test temperature range from  $T_0$  to  $T$ . For most alloys and metals this is

$$\text{Resistance per Meter} = \frac{\text{Resistivity } (\Omega \cdot \text{mm}^2 \cdot \text{m}^{-1})}{\text{Cross-sectional area } (\text{mm}^2)} = \Omega \cdot \text{m}^{-1}$$



Graph 1

not the case (Graph 1), especially regarding large temperature intervals. In order to deliver an exact description of the temperature dependence of the resistivity, complicated equations are required.

In spite of this the temperature coefficient is defined from the equation above as being:

$$\alpha = \frac{R_t - R_0}{R_0 (T - T_0)} \quad [K^{-1}]$$

It thus indicates the average variation of the resistivity per degree Kelvin in the temperature range from  $T_0$  to  $T$ , referred to in the resistance value  $R$  at  $T_0$ .

When experimentally determining the temperature coefficient as well as during communication between

supplier and customer, two points must be observed:

1. As already mentioned, the temperature dependence of the resistivity in general does not show a linear, but a curved form. This applies particularly to certain resistance alloys and is the reason why different temperature coefficients result from the calculations, because they depend on the part of the curve which corresponds to a certain  $\Delta t$  (see Graph 1 on page 62).
2. Due to the fact that the temperature-dependent resistance variation is referred to the resistance value  $R_0$  when defining the temperature coefficient, different temperature coefficient values

result from different values of  $R_0$ , even if the temperature intervals chosen are of equal width.

This means that together with the value of the temperature coefficient the temperature interval must always be quoted.

For example:

TC 20 °C to 105 °C = +50 ppm/K

Comparison of test results is possible only if the test conditions are the same.

In some alloys the temperature coefficient can be controlled by combining certain alloy components. It can then achieve negative values or values around 0 ppm/K between room temperature and approx. 100 °C.

### Dependence of Resistivity in $\mu\Omega \cdot \text{cm}$ on Temperature for Various Alloys

| Alloy          | 20 °C               | 100 °C | 200 °C | 300 °C | 400 °C | 500 °C | 600 °C | 700 °C | 800 °C | 900 °C | 1000 °C | 1100 °C | 1200 °C |
|----------------|---------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|---------|---------|---------|
| ISA OHM®       | 132                 | 132    | 132    | -      | -      | -      | -      | -      | -      | -      | -       | -       | -       |
| ISA®-CHROM 60  | 113 <sup>1)</sup>   | 114    | 116    | 118    | 120    | 122    | 121    | 121    | 122    | 123    | 124     | 126     | 128     |
|                | (111) <sup>2)</sup> | (112)  | (114)  | (116)  | (118)  | (122)  | -      | -      | -      | -      | -       | -       | -       |
| ISA®-CHROM 80  | 112 <sup>1)</sup>   | 113    | 113    | 114    | 115    | 116    | 115    | 114    | 114    | 114    | 115     | 116     | 117     |
|                | (108) <sup>2)</sup> | (109)  | (110)  | (112)  | (114)  | (116)  | -      | -      | -      | -      | -       | -       | -       |
| ISA®-CHROM 30  | 104                 | 107    | 111    | 114    | 117    | 120    | 122    | 124    | 126    | 128    | 130     | 132     | -       |
| ISOTAN®        | 49                  | 49     | 49     | 49     | 49     | 49     | -      | -      | -      | -      | -       | -       | -       |
| ISA®-NICKEL    | 49                  | 51     | 53     | 55     | 56     | 57     | 59     | 60     | -      | -      | -       | -       | -       |
| MANGANIN®      | 43                  | 43     | -      | -      | -      | -      | -      | -      | -      | -      | -       | -       | -       |
| NICKELIN-W     | 40                  | 40.4   | 41     | 41.7   | 42.4   | 43.2   | -      | -      | -      | -      | -       | -       | -       |
| RESISTHERM®    | 33                  | 41     | 52     | 64     | 76     | 89     | 102    | -      | -      | -      | -       | -       | -       |
| ISA®-ZIN       | 30                  | 30.4   | 31     | 31.5   | 32.1   | 32.6   | -      | -      | -      | -      | -       | -       | -       |
| ZERANIN® 30    | 29                  | 29     | -      | -      | -      | -      | -      | -      | -      | -      | -       | -       | -       |
| ALLOY 127      | 21                  | 21.5   | 22.1   | 22.8   | 23.4   | -      | -      | -      | -      | -      | -       | -       | -       |
| ALLOY 90       | 15                  | 15.6   | 16.2   | 16.9   | 17.5   | -      | -      | -      | -      | -      | -       | -       | -       |
| ISA® 13        | 12.5                | 12.9   | 13.3   | -      | -      | -      | -      | -      | -      | -      | -       | -       | -       |
| ALLOY 60       | 10                  | 10.7   | 11.4   | 12.3   | -      | -      | -      | -      | -      | -      | -       | -       | -       |
| NI 99,2        | 9                   | 13     | 19     | 26     | 33     | 38     | -      | -      | -      | -      | -       | -       | -       |
| PURE NICKEL    | 8                   | 12     | 18     | 25     | 32     | 36     | -      | -      | -      | -      | -       | -       | -       |
| SPECIAL NICKEL | 7.65                | 11.1   | 16.6   | -      | -      | -      | -      | -      | -      | -      | -       | -       | -       |
| ALLOY 30       | 5                   | 5.7    | 6.4    | -      | -      | -      | -      | -      | -      | -      | -       | -       | -       |
| A-COPPER       | 2.5                 | 3.1    | 3.9    | -      | -      | -      | -      | -      | -      | -      | -       | -       | -       |
| PURE COPPER    | 1.72                | 2.3    | 3.1    | -      | -      | -      | -      | -      | -      | -      | -       | -       | -       |

1) These values apply to a state of equilibrium.

2) These values apply to a state after rapid cooling; see also B. "Special Characteristics of Nickel-Chromium Alloys".

## B. Special Characteristics of Nickel-Chromium Alloys


The resistivity of nickel-chromium alloys shows a special characteristic. At temperatures below 500 °C it is affected by the cooling rate, e. g. after annealing, and it decreases with increasing cooling rate. This behaviour is shown schematically in the graph on the right.

The solid line represents the so-called state of equilibrium, i. e. the resistivity of an annealed wire after slow cooling. The dotted line indicates how the resistivity below 500 °C changes for lower values by rapid cooling. Rapid cooling takes place e. g. with thin wires after strand annealing.

The best effect is achieved with wires of non-ferrous nickel-chromium alloys, like ISA<sup>®</sup>-CHROM 80. It is weaker for nickel-chromium ISA<sup>®</sup>-CHROM 60 and can be neglected for nickel-chromium ISA<sup>®</sup>-CHROM 30.

In addition, since with normal strand annealing the cooling rate increases with decreasing wire diameter, this effect will become stronger, too, as the wire diameter becomes smaller.

For ISA<sup>®</sup>-CHROM 80 and ISA<sup>®</sup>-



*Effect of Pre-Treatment on the Temperature Dependence of the Resistance on ISA<sup>®</sup>-CHROM 80 (NiCr8020).*

CHROM 60, assuming normal annealing conditions, the resistance decrease between 1 and 0.01 mm  $\varnothing$  amounts to approx. 1.3 % resp. 0.5 %. For ISA<sup>®</sup>OHM the decrease is approx. 5 % because of a varying composition.

For resistance wires of NiCr alloys no sliding resistivity has been standardized; instead an average resistivity is quoted (see also DIN 17471). It should be borne in mind, however, that this value for ISA<sup>®</sup>-CHROM 80 and ISA<sup>®</sup>-CHROM 60 is lower than the value quoted in DIN 17470 for heating resistors.

# C. Surface Loading Capacity

Generation of heat has great importance in electrical engineering, no matter whether it should be controlled as far as possible or whether it is intended to be used.

The main question to be answered in this connection is what temperature a current-carrying wire, ribbon, sheet etc. will reach during operation.

Answering this question is somewhat difficult, since the determining factors, like type of insulation and shape of the resistive conductor, cooling conditions, surface deterioration during operation and other properties of the material, which for their part again depend on the temperature, can often only be a matter for conjecture.

## Current-Carrying Capacity of Wires

In order to make things easier to control, simple models, suitable to be converted into practical solutions, are chosen for tests and measurements. Such a model is formed e. g. by a straight bare wire, stretched in still air of 20 °C, whereby the natural movement of the air is in no way impeded, and which is loaded by current. This model has the advantage that the temperature of the wire can be determined on the basis of its thermal expansion in addition to other methods.

If a current  $i$  flows through a conductor with the length  $l$  and the resistance  $R$ , the electrical power  $P$ , converted into heat, is calculated as follows:

$$P = i^2 \cdot R$$

Inserting

$$R = \rho \cdot \frac{l}{S}$$

the following results:

$$P = \frac{i^2 \cdot \rho \cdot l \cdot 4}{\pi \cdot d^2}$$

The amount of heat created per cm<sup>2</sup> of wire surface is called the surface load  $n$  of the wire.

Using the above formula, then after inserting the determining values for the surface in the following results:

$$n = \frac{i^2 \cdot \rho_t \cdot 0.04053}{d^3}$$

$n$  = Surface load in W · cm<sup>2</sup>

$i$  = Current in Ampere

$\rho_t$  = Resistivity in  $\Omega \cdot \text{mm}^2 \cdot \text{m}^{-1}$  at temperature  $T$  (°C)

$d$  = Wire diameter in mm

The surface load is a measure of the temperature the wire will achieve under given environmental conditions. It is not a material-dependent quality, but must be chosen in accordance with the respective conductor material and application.

The upper limit should, of course, be determined on the basis of the maximum working temperature of the conductor in order to ensure adequate scale and corrosion resistance etc.

Fig. 1 shows the relationships between surface load and wire operating temperature for wires of different materials with 0.5 mm  $\varnothing$ .

In general, a current-carrying wire very quickly achieves, after switching-on the current, a steady state, in which the amount of heat produced within a unit of time equals the amount of heat dissipated. When using the model mentioned above: "Stretched wire in still air of 20 °C", the heat is dissipated by convection – removal through air flow – and radiation. Under the conditions quoted the heat is removed mainly by convection, while heat removal by radiation is worth mentioning only at temperatures >400 to 600 °C. The share of heat radiation, however, increases with temperature by a factor of  $T^4$ .




Fig. 1: Overtemperature of Wire against Air in Dependence on the Surface Load in Watt/cm<sup>2</sup> and on Different Materials.

The diameter of the conductor, too, affects the kind of heat dissipation. Fig. 2 shows the interaction of convection and radiation in dependence on the wire diameter. In the area of the hatched border line heat removal by convection equals that by radiation. At lower temperatures and smaller wire diameters heat removal by convection prevails; at higher temperatures and larger wire diameters heat removal by radiation is in excess.

Fig. 2 also shows that the share of convection in heat dissipation grows with decreasing wire diameter. This is due to the fact that for thinner wires the heat transfer from wire to air improves considerably. In practice this means that, for the same operating temperature, thin wires can be loaded more heavily than thick wires.

By suppressing convection, e. g. by lowering the atmospheric pressure, the curve is shifted to the left; this means that the share of radiation increases. On the other hand the curve can be shifted to the right e. g. by using a fan. Provided the electrical power is kept constant, in the latter case the wire temperature would be substantially lower.

As mentioned before, the diagrams – figs. 1 and 2 – apply to horizontally arranged straight wires in still air. In practice this arrangement is very rarely chosen, especially for thin wires. Wires wound on cores or arranged in the form of a spiral permit much smaller surface loads since the heat dissipating wire surface is strongly reduced as compared with freely stretched wires.




Fig. 2  
Comparison of the share of radiation and convection effects in heat dissipation of resistance wires in air at 20 °C. In the dark boundary area heat dissipation by convection equals that by radiation. On the right of the boundary area radiation prevails; on the left convection has the larger share.

In case of a bobbin being densely wound with resistance wire, the surface of this structure can be taken as the reference quantity for the value “Watt per cm<sup>2</sup>”. This means that the diameter of the wound bobbin can be taken as “wire diameter”. The result is that for such a structure at a given surface load in W/cm<sup>2</sup> the surface temperature will be considerably higher than for a single wire.

Fig. 3 shows the possible current-carrying capacity in Watt/cm<sup>2</sup> for different temperatures dependent on the “wire” diameter. Bobbins should be referred to in this diagram by the bobbin diameter. Since the current-carrying capacity in W/cm<sup>2</sup> is given, this diagram applies to all Isabellenhütte alloys. The interrelationship between current loads (Ampere) and resulting

temperature for an ISOTAN® wire of 0.5 mm diam. can be seen from Fig. 4. It must be kept in mind, however, that for this type of presentation the curves for materials with different resistivities are also different, unlike the previous figures.

As shown in fig. 1, a given surface load – expressed in W/cm<sup>2</sup> – causes equal wire temperatures for every alloy. Therefore the current load values for equal wire diameters can be converted by the following formula:

$$P = \text{constant, thus } i_1^2 \cdot R_1 = i_2^2 \cdot R_2$$

$$\text{Thus: } i_1 = i_2 \cdot \sqrt{\frac{R_2}{R_1}}$$

$$\text{and } i_1 = i_2 \cdot \sqrt{\frac{\rho_2}{\rho_1}}$$




Fig. 3

The following tables show, with ISOTAN® as an example, the geometrical data between 0.02 and 6.3 mm diam. as well as the current-carrying capacity values in Ampere for 40/60/80/100/200/300/400/500 and 600 °C.

In accordance with the above formula, the current values are converted in accordance with:

$$i_x = i_{\text{ISOTAN}} \cdot \sqrt{\frac{0.49}{\rho_x}}$$

where  $i_x$  refers to the current for a wire of an alloy with the resistivity  $\rho_x$ . It must be kept in mind that for  $\rho_x$  the values valid for the respective temperature must be used (see tables on pages 66 and 67).

The current-carrying capacity tables all refer to bare wire; due to better heat dissipation, oxidized wires (only possible for the alloys ISA®-CHROM 60, ISA®-CHROM 80 and ISOTAN®) can withstand a load increase of up to 20 %, expressed in W/cm², mainly at higher temperatures.

The current-carrying capacities of enamelled wires are about the same as those of bare wires. The heat insulation effect of the enamel is compensated by the increase of the effective diameter and good heat dissipation

properties. Silk-covered wires exhibit strongly varying loading capacities, depending on the kind of manufacturing process and type; the respective value must be determined individually.




Fig. 4: Current-carrying capacity of ISOTAN® wire of 0.5 mm diam. in dependence on overtemperature of the wire against air at 20 °C (100 °C overtemperature correspond to a real temperature of 120 °C).

| Diameter<br>in mm | ISOTAN®<br>Resistance<br>$\Omega \cdot m^{-1}$ | Ampere for an Overtemperature of: |                                      |        |                                      |        |                                      |        |                                      |        |                                      |
|-------------------|--|-----------------------------------|--------------------------------------|--------|--------------------------------------|--------|--------------------------------------|--------|--------------------------------------|--------|--------------------------------------|
|                   |  | 40°C                              |                                      | 60°C   |                                      | 80°C   |                                      | 100°C  |                                      | 200°C  |                                      |
|                   |  | i in A                            | Surface Load<br>in W/cm <sup>2</sup> | i in A | Surface Load<br>in W/cm <sup>2</sup> | i in A | Surface Load<br>in W/cm <sup>2</sup> | i in A | Surface Load<br>in W/cm <sup>2</sup> | i in A | Surface Load<br>in W/cm <sup>2</sup> |
| 0.020             | 1560   | 0.0270                            | 1.82                                 | 0.0342 | 2.92                                 | 0.0410 | 4.20                                 | 0.0479 | 5.69                                 | 0.0724 | 13.0                                 |
| 0.022             | 1290   | 0.0305                            | 1.75                                 | 0.0381 | 2.74                                 | 0.0450 | 3.82                                 | 0.0534 | 5.31                                 | 0.0807 | 12.1                                 |
| 0.025             | 998  | 0.0353                            | 1.60                                 | 0.0441 | 2.49                                 | 0.0520 | 3.47                                 | 0.0617 | 4.84                                 | 0.0933 | 11.1                                 |
| 0.028             | 796  | 0.0402                            | 1.48                                 | 0.0502 | 2.30                                 | 0.0600 | 3.29                                 | 0.0703 | 4.46                                 | 0.106  | 10.2                                 |
| (0.030)           | 693  | 0.0437                            | 1.41                                 | 0.0546 | 2.21                                 | 0.0650 | 3.13                                 | 0.0764 | 4.29                                 | 0.115  | 9.70                                 |
| 0.032             | 609  | 0.0467                            | 1.33                                 | 0.0584 | 2.08                                 | 0.0690 | 2.90                                 | 0.0818 | 4.05                                 | 0.124  | 9.26                                 |
| 0.036             | 481  | 0.0534                            | 1.22                                 | 0.0668 | 1.92                                 | 0.0790 | 2.68                                 | 0.0935 | 3.72                                 | 0.140  | 8.51                                 |
| 0.040             | 390  | 0.0606                            | 1.15                                 | 0.0757 | 1.79                                 | 0.0900 | 2.53                                 | 0.106  | 3.45                                 | 0.160  | 7.89                                 |
| 0.045             | 308  | 0.0691                            | 1.05                                 | 0.0864 | 1.64                                 | 0.102  | 2.28                                 | 0.121  | 3.17                                 | 0.183  | 7.26                                 |
| 0.050             | 249  | 0.0777                            | 0.966                                | 0.0971 | 1.51                                 | 0.115  | 2.12                                 | 0.136  | 2.94                                 | 0.206  | 6.74                                 |
| 0.056             | 199  | 0.0880                            | 0.880                                | 0.110  | 1.38                                 | 0.130  | 1.92                                 | 0.154  | 2.68                                 | 0.235  | 6.22                                 |
| (0.060)           | 173  | 0.0960                            | 0.853                                | 0.120  | 1.33                                 | 0.142  | 1.87                                 | 0.168  | 2.58                                 | 0.254  | 5.93                                 |
| 0.063             | 157  | 0.101                             | 0.816                                | 0.126  | 1.27                                 | 0.150  | 1.80                                 | 0.177  | 2.49                                 | 0.269  | 5.73                                 |
| (0.070)           | 127  | 0.114                             | 0.758                                | 0.143  | 1.19                                 | 0.169  | 1.67                                 | 0.200  | 2.32                                 | 0.303  | 5.33                                 |
| 0.071             | 124  | 0.116                             | 0.752                                | 0.145  | 1.17                                 | 0.172  | 1.65                                 | 0.203  | 2.29                                 | 0.308  | 5.27                                 |
| 0.080             | 97.5   | 0.133                             | 0.691                                | 0.166  | 1.08                                 | 0.197  | 1.52                                 | 0.233  | 2.11                                 | 0.354  | 4.86                                 |
| 0.090             | 77.0   | 0.153                             | 0.642                                | 0.191  | 1.00                                 | 0.226  | 1.40                                 | 0.267  | 1.94                                 | 0.406  | 4.48                                 |
| 0.100             | 62.4   | 0.173                             | 0.600                                | 0.216  | 0.933                                | 0.254  | 1.29                                 | 0.302  | 1.81                                 | 0.458  | 4.17                                 |
| (0.110)           | 51.6   | 0.193                             | 0.560                                | 0.241  | 0.873                                | 0.286  | 1.23                                 | 0.337  | 1.69                                 | 0.512  | 3.91                                 |
| 0.112             | 49.7   | 0.197                             | 0.554                                | 0.246  | 0.865                                | 0.292  | 1.22                                 | 0.345  | 1.68                                 | 0.523  | 3.86                                 |
| (0.120)           | 43.3   | 0.213                             | 0.524                                | 0.266  | 0.818                                | 0.315  | 1.15                                 | 0.372  | 1.59                                 | 0.567  | 3.69                                 |
| 0.125             | 39.9   | 0.223                             | 0.510                                | 0.279  | 0.798                                | 0.331  | 1.12                                 | 0.391  | 1.55                                 | 0.594  | 3.59                                 |
| (0.130)           | 36.9   | 0.234                             | 0.498                                | 0.292  | 0.775                                | 0.347  | 1.09                                 | 0.409  | 1.51                                 | 0.622  | 3.50                                 |
| 0.140             | 31.8   | 0.255                             | 0.475                                | 0.319  | 0.742                                | 0.378  | 1.04                                 | 0.446  | 1.44                                 | 0.679  | 3.33                                 |
| (0.150)           | 27.7   | 0.276                             | 0.452                                | 0.345  | 0.706                                | 0.409  | 0.993                                | 0.483  | 1.37                                 | 0.736  | 3.18                                 |
| 0.160             | 24.4   | 0.297                             | 0.430                                | 0.371  | 0.671                                | 0.441  | 0.949                                | 0.520  | 1.31                                 | 0.794  | 3.05                                 |
| 0.180             | 19.3   | 0.342                             | 0.401                                | 0.428  | 0.628                                | 0.508  | 0.885                                | 0.599  | 1.22                                 | 0.911  | 2.83                                 |
| 0.200             | 15.6   | 0.386                             | 0.372                                | 0.482  | 0.581                                | 0.572  | 0.818                                | 0.675  | 1.13                                 | 1.03   | 2.64                                 |
| (0.220)           | 12.9   | 0.433                             | 0.354                                | 0.541  | 0.552                                | 0.642  | 0.778                                | 0.758  | 1.07                                 | 1.16   | 2.49                                 |
| 0.224             | 12.4   | 0.441                             | 0.347                                | 0.551  | 0.542                                | 0.653  | 0.761                                | 0.771  | 1.05                                 | 1.18   | 2.46                                 |
| 0.250             | 9.98   | 0.503                             | 0.324                                | 0.629  | 0.507                                | 0.746  | 0.713                                | 0.880  | 0.982                                | 1.35   | 2.30                                 |
| 0.280             | 7.96   | 0.577                             | 0.303                                | 0.721  | 0.473                                | 0.856  | 0.666                                | 1.01   | 0.914                                | 1.54   | 2.14                                 |
| (0.300)           | 6.93   | 0.623                             | 0.287                                | 0.778  | 0.448                                | 0.924  | 0.632                                | 1.12   | 0.875                                | 1.67   | 2.06                                 |
| 0.315             | 6.29   | 0.663                             | 0.281                                | 0.828  | 0.438                                | 0.983  | 0.612                                | 1.16   | 0.849                                | 1.77   | 2.00                                 |
| (0.320)           | 6.09   | 0.672                             | 0.275                                | 0.843  | 0.433                                | 1.00   | 0.609                                | 1.18   | 0.841                                | 1.81   | 1.98                                 |
| (0.350)           | 5.09   | 0.748                             | 0.261                                | 0.936  | 0.406                                | 1.11   | 0.574                                | 1.31   | 0.796                                | 2.01   | 1.87                                 |
| 0.355             | 4.95   | 0.760                             | 0.258                                | 0.950  | 0.404                                | 1.13   | 0.571                                | 1.33   | 0.789                                | 2.05   | 1.86                                 |
| 0.40              | 3.90   | 0.880                             | 0.242                                | 1.10   | 0.378                                | 1.31   | 0.536                                | 1.54   | 0.734                                | 2.37   | 1.73                                 |
| 0.45              | 3.08   | 1.01                              | 0.224                                | 1.26   | 0.349                                | 1.50   | 0.494                                | 1.77   | 0.684                                | 2.73   | 1.62                                 |
| 0.50              | 2.49   | 1.15                              | 0.212                                | 1.44   | 0.332                                | 1.70   | 0.462                                | 2.01   | 0.644                                | 3.10   | 1.53                                 |
| (0.55)            | 2.06   | 1.29                              | 0.200                                | 1.61   | 0.315                                | 1.92   | 0.444                                | 2.26   | 0.609                                | 3.49   | 1.45                                 |
| 0.56              | 1.99   | 1.32                              | 0.198                                | 1.65   | 0.309                                | 1.95   | 0.432                                | 2.31   | 0.603                                | 3.57   | 1.44                                 |
| (0.60)            | 1.73   | 1.43                              | 0.189                                | 1.79   | 0.297                                | 2.13   | 0.420                                | 2.51   | 0.580                                | 3.88   | 1.39                                 |
| 0.63              | 1.57   | 1.53                              | 0.187                                | 1.91   | 0.292                                | 2.26   | 0.409                                | 2.67   | 0.565                                | 4.12   | 1.35                                 |
| (0.65)            | 1.48   | 1.58                              | 0.182                                | 1.98   | 0.285                                | 2.35   | 0.402                                | 2.77   | 0.555                                | 4.29   | 1.33                                 |
| (0.70)            | 1.27   | 1.74                              | 0.177                                | 2.17   | 0.275                                | 2.58   | 0.388                                | 3.04   | 0.533                                | 4.70   | 1.28                                 |
| 0.71              | 1.24   | 1.77                              | 0.175                                | 2.21   | 0.273                                | 2.62   | 0.383                                | 3.09   | 0.529                                | 4.78   | 1.27                                 |
| 0.75              | 1.11   | 1.89                              | 0.169                                | 2.36   | 0.264                                | 2.81   | 0.374                                | 3.31   | 0.514                                | 5.12   | 1.23                                 |
| 0.80              | 0.975  | 2.05                              | 0.164                                | 2.56   | 0.256                                | 3.03   | 0.359                                | 3.58   | 0.496                                | 5.55   | 1.19                                 |
| 0.85              | 0.864  | 2.21                              | 0.159                                | 2.76   | 0.248                                | 3.27   | 0.348                                | 3.86   | 0.481                                | 5.99   | 1.16                                 |
| 0.90              | 0.770  | 2.37                              | 0.154                                | 2.96   | 0.240                                | 3.51   | 0.338                                | 4.14   | 0.467                                | 6.43   | 1.13                                 |
| 0.95              | 0.691  | 2.53                              | 0.149                                | 3.16   | 0.233                                | 3.75   | 0.328                                | 4.43   | 0.454                                | 6.89   | 1.10                                 |
| 1.00              | 0.624  | 2.70                              | 0.146                                | 3.37   | 0.227                                | 4.00   | 0.320                                | 4.72   | 0.442                                | 7.35   | 1.07                                 |
| (1.10)            | 0.516  | 3.04                              | 0.139                                | 3.80   | 0.217                                | 4.51   | 0.306                                | 5.32   | 0.422                                | 8.30   | 1.03                                 |
| 1.12              | 0.497  | 3.11                              | 0.138                                | 3.88   | 0.215                                | 4.61   | 0.304                                | 5.44   | 0.418                                | 8.49   | 1.02                                 |
| (1.20)            | 0.433  | 3.39                              | 0.133                                | 4.24   | 0.208                                | 5.03   | 0.292                                | 5.94   | 0.405                                | 9.27   | 0.986                                |
| 1.25              | 0.399  | 3.57                              | 0.131                                | 4.46   | 0.204                                | 5.30   | 0.288                                | 6.25   | 0.397                                | 9.77   | 0.969                                |
| 1.40              | 0.318  | 4.12                              | 0.124                                | 5.16   | 0.194                                | 6.12   | 0.273                                | 7.22   | 0.377                                | 11.3   | 0.923                                |
| 1.50              | 0.277  | 4.50                              | 0.120                                | 5.63   | 0.188                                | 6.68   | 0.265                                | 7.88   | 0.365                                | 12.3   | 0.896                                |
| 1.60              | 0.244  | 4.89                              | 0.117                                | 6.11   | 0.182                                | 7.25   | 0.256                                | 8.56   | 0.355                                | 13.4   | 0.873                                |
| 1.80              | 0.193  | 5.69                              | 0.110                                | 7.12   | 0.174                                | 8.43   | 0.244                                | 9.95   | 0.337                                | 15.7   | 0.833                                |
| 2.00              | 0.156  | 6.50                              | 0.106                                | 8.14   | 0.166                                | 9.66   | 0.233                                | 11.4   | 0.323                                | 17.9   | 0.800                                |
| (2.20)            | 0.129  | 7.37                              | 0.102                                | 9.21   | 0.160                                | 10.9   | 0.224                                | 12.9   | 0.311                                | 20.4   | 0.773                                |
| 2.24              | 0.124  | 7.54                              | 0.101                                | 9.43   | 0.159                                | 11.2   | 0.222                                | 13.2   | 0.307                                | 20.9   | 0.768                                |
| 2.50              | 0.0998   | 8.74                              | 0.098                                | 10.9   | 0.152                                | 13.0   | 0.217                                | 15.3   | 0.296                                | 24.1   | 0.739                                |
| 2.80              | 0.0796   | 10.1                              | 0.094                                | 12.6   | 0.144                                | 15.0   | 0.205                                | 17.7   | 0.284                                | 28.1   | 0.712                                |
| 3.00              | 0.0693   | 11.1                              | 0.092                                | 13.9   | 0.143                                | 16.4   | 0.199                                | 19.4   | 0.277                                | 30.7   | 0.696                                |
| 3.15              | 0.0629   | 11.8                              | 0.089                                | 14.8   | 0.140                                | 17.5   | 0.198                                | 20.7   | 0.272                                | 32.9   | 0.685                                |
| (3.20)            | 0.0609   | 12.1                              | 0.089                                | 15.1   | 0.139                                | 18.0   | 0.197                                | 21.2   | 0.271                                | 33.6   | 0.682                                |
| (3.50)            | 0.0509   | 13.6                              | 0.086                                | 17.1   | 0.137                                | 20.2   | 0.190                                | 23.8   | 0.263                                | 37.9   | 0.664                                |
| 3.55              | 0.0495   | 13.9                              | 0.086                                | 17.4   | 0.135                                | 20.6   | 0.189                                | 24.3   | 0.262                                | 38.6   | 0.661                                |
| 4.00              | 0.0390   | 16.3                              | 0.083                                | 20.4   | 0.130                                | 24.1   | 0.181                                | 28.5   | 0.252                                | 45.4   | 0.639                                |
| 4.50              | 0.0308   | 19.1                              | 0.080                                | 23.8   | 0.124                                | 28.3   | 0.176                                | 33.4   | 0.243                                | 53.3   | 0.619                                |
| 5.00              | 0.0249   | 22.0                              | 0.077                                | 27.6   | 0.122                                | 32.7   | 0.171                                | 38.6   | 0.236                                | 61.6   | 0.602                                |
| 5.50              | 0.0206   | 25.0                              | 0.075                                | 31.3   | 0.118                                | 37.1   | 0.166                                | 43.8   | 0.229                                | 70.3   | 0.589                                |
| 5.60              | 0.0199   | 25.7                              | 0.075                                | 32.1   | 0.117                                | 38.1   | 0.165                                | 44.9   | 0.228                                | 72.0   | 0.586                                |
| 6.00              | 0.0173   | 28.2                              | 0.074                                | 35.3   | 0.115                                | 41.9   | 0.162                                | 49.4   | 0.224                                | 79.2   | 0.577                                |
| 6.30              | 0.0157   | 30.2                              | 0.073                                | 37.8   | 0.114                                | 44.8   | 0.161                                | 52.9   | 0.222                                | 84.8   | 0.571                                |

| Ampere for an Overtemperature of: |                                      |        |                                      |        |                                      |        |                                      | ISOTAN®<br>Resistance<br>$\Omega \cdot m^{-1}$ | Diameter<br>in mm |
|-----------------------------------|--------------------------------------|--------|--------------------------------------|--------|--------------------------------------|--------|--------------------------------------|--|-------------------|
| 300 °C                            |                                      | 400 °C |                                      | 500 °C |                                      | 600 °C |                                      |  |                   |
| i in A                            | Surface Load<br>in W/cm <sup>2</sup> | i in A | Surface Load<br>in W/cm <sup>2</sup> | i in A | Surface Load<br>in W/cm <sup>2</sup> | i in A | Surface Load<br>in W/cm <sup>2</sup> |  |                   |
| 0.0964                            | 23.0                                 | 0.110  | 30.1                                 | 0.133  | 44.2                                 | 0.144  | 51.2                                 | 1560   | 0.020             |
| 0.109                             | 22.2                                 | 0.123  | 28.2                                 | 0.149  | 41.4                                 | 0.161  | 48.3                                 | 1290   | 0.022             |
| 0.124                             | 19.6                                 | 0.143  | 25.9                                 | 0.173  | 38.0                                 | 0.188  | 44.7                                 | 998  | 0.025             |
| 0.138                             | 18.1                                 | 0.163  | 24.0                                 | 0.197  | 35.2                                 | 0.215  | 41.7                                 | 796  | 0.028             |
| 0.153                             | 17.2                                 | 0.177  | 22.9                                 | 0.214  | 33.7                                 | 0.233  | 40.0                                 | 693  | (0.030)           |
| 0.165                             | 16.4                                 | 0.191  | 22.0                                 | 0.231  | 32.2                                 | 0.252  | 38.5                                 | 609  | 0.032             |
| 0.188                             | 15.1                                 | 0.219  | 20.3                                 | 0.265  | 29.8                                 | 0.290  | 35.8                                 | 481  | 0.036             |
| 0.212                             | 14.0                                 | 0.247  | 19.0                                 | 0.300  | 27.8                                 | 0.329  | 33.6                                 | 390  | 0.040             |
| 0.243                             | 12.9                                 | 0.284  | 17.6                                 | 0.344  | 25.8                                 | 0.379  | 31.4                                 | 308  | 0.045             |
| 0.274                             | 11.9                                 | 0.321  | 16.4                                 | 0.389  | 24.0                                 | 0.431  | 29.4                                 | 249  | 0.050             |
| 0.312                             | 11.0                                 | 0.367  | 15.2                                 | 0.445  | 22.3                                 | 0.494  | 27.6                                 | 199  | 0.056             |
| 0.338                             | 10.5                                 | 0.398  | 14.6                                 | 0.482  | 21.4                                 | 0.537  | 26.5                                 | 173  | (0.060)           |
| 0.358                             | 10.2                                 | 0.422  | 14.1                                 | 0.511  | 20.7                                 | 0.569  | 25.7                                 | 157  | 0.063             |
| 0.404                             | 9.43                                 | 0.478  | 13.2                                 | 0.578  | 19.3                                 | 0.646  | 24.1                                 | 127  | (0.070)           |
| 0.411                             | 9.34                                 | 0.486  | 13.1                                 | 0.588  | 19.2                                 | 0.658  | 24.0                                 | 124  | 0.071             |
| 0.471                             | 8.60                                 | 0.559  | 12.1                                 | 0.677  | 17.8                                 | 0.760  | 22.4                                 | 97.5   | 0.080             |
| 0.540                             | 7.94                                 | 0.648  | 11.4                                 | 0.785  | 16.8                                 | 0.877  | 20.9                                 | 77.0   | 0.090             |
| 0.610                             | 7.39                                 | 0.728  | 10.5                                 | 0.882  | 15.4                                 | 0.966  | 19.7                                 | 62.4   | 0.100             |
| 0.682                             | 6.93                                 | 0.816  | 9.92                                 | 0.985  | 14.5                                 | 1.12   | 18.7                                 | 51.6   | (0.110)           |
| 0.696                             | 6.84                                 | 0.833  | 9.81                                 | 1.01   | 14.4                                 | 1.15   | 18.5                                 | 49.7   | 0.112             |
| 0.754                             | 6.53                                 | 0.905  | 9.40                                 | 1.10   | 13.8                                 | 1.25   | 17.8                                 | 43.3   | (0.120)           |
| 0.791                             | 6.36                                 | 0.950  | 9.16                                 | 1.15   | 13.4                                 | 1.31   | 17.4                                 | 39.9   | 0.125             |
| 0.828                             | 6.20                                 | 0.995  | 8.95                                 | 1.21   | 13.1                                 | 1.37   | 17.1                                 | 36.9   | (0.130)           |
| 0.903                             | 5.90                                 | 1.09   | 8.55                                 | 1.32   | 12.5                                 | 1.51   | 16.4                                 | 31.8   | 0.140             |
| 0.979                             | 5.64                                 | 1.18   | 8.20                                 | 1.43   | 12.0                                 | 1.64   | 15.8                                 | 27.7   | (0.150)           |
| 1.06                              | 5.40                                 | 1.28   | 7.89                                 | 1.55   | 11.6                                 | 1.77   | 15.3                                 | 24.4   | 0.160             |
| 1.21                              | 5.01                                 | 1.47   | 7.35                                 | 1.78   | 10.8                                 | 2.05   | 14.3                                 | 19.3   | 0.180             |
| 1.37                              | 4.68                                 | 1.67   | 6.91                                 | 2.02   | 10.1                                 | 2.34   | 13.6                                 | 15.6   | 0.200             |
| 1.54                              | 4.41                                 | 1.87   | 6.54                                 | 2.27   | 9.59                                 | 2.63   | 12.9                                 | 12.9   | (0.220)           |
| 1.57                              | 4.36                                 | 1.91   | 6.47                                 | 2.32   | 9.49                                 | 2.69   | 12.8                                 | 12.4   | 0.224             |
| 1.79                              | 4.07                                 | 2.19   | 6.07                                 | 2.65   | 8.91                                 | 3.08   | 12.1                                 | 9.98   | 0.250             |
| 2.05                              | 3.80                                 | 2.51   | 5.70                                 | 3.04   | 8.35                                 | 3.55   | 11.4                                 | 7.96   | 0.280             |
| 2.23                              | 3.64                                 | 2.73   | 5.48                                 | 3.31   | 8.04                                 | 3.87   | 11.0                                 | 6.93   | (0.300)           |
| 2.36                              | 3.54                                 | 2.90   | 5.33                                 | 3.51   | 7.82                                 | 4.12   | 10.8                                 | 6.29   | 0.315             |
| 2.41                              | 3.50                                 | 2.96   | 5.29                                 | 3.58   | 7.76                                 | 4.20   | 10.7                                 | 6.09   | (0.320)           |
| 2.68                              | 3.32                                 | 3.30   | 5.04                                 | 4.00   | 7.39                                 | 4.70   | 10.2                                 | 5.09   | (0.350)           |
| 2.72                              | 3.29                                 | 3.36   | 5.00                                 | 4.07   | 7.33                                 | 4.79   | 10.2                                 | 4.95   | 0.355             |
| 3.15                              | 3.07                                 | 3.89   | 4.69                                 | 4.71   | 6.87                                 | 5.57   | 9.60                                 | 3.90   | 0.40              |
| 3.63                              | 2.87                                 | 4.50   | 4.40                                 | 5.45   | 6.46                                 | 6.46   | 9.09                                 | 3.08   | 0.45              |
| 4.13                              | 2.71                                 | 5.13   | 4.17                                 | 6.21   | 6.12                                 | 7.39   | 8.69                                 | 2.49   | 0.50              |
| 4.64                              | 2.57                                 | 5.77   | 3.97                                 | 6.99   | 5.83                                 | 8.35   | 8.31                                 | 2.06   | (0.55)            |
| 4.75                              | 2.55                                 | 5.91   | 3.94                                 | 7.15   | 5.78                                 | 8.54   | 8.24                                 | 1.99   | 0.56              |
| 5.17                              | 2.45                                 | 6.44   | 3.81                                 | 7.80   | 5.58                                 | 9.33   | 8.00                                 | 1.73   | (0.60)            |
| 5.49                              | 2.39                                 | 6.84   | 3.72                                 | 8.29   | 5.45                                 | 9.94   | 7.83                                 | 1.57   | 0.63              |
| 5.70                              | 2.35                                 | 7.18   | 3.66                                 | 8.62   | 5.37                                 | 10.3   | 7.73                                 | 1.48   | (0.65)            |
| 6.26                              | 2.26                                 | 7.81   | 3.53                                 | 9.46   | 5.18                                 | 11.4   | 7.49                                 | 1.27   | (0.70)            |
| 6.37                              | 2.25                                 | 7.96   | 3.51                                 | 9.63   | 5.15                                 | 11.6   | 7.45                                 | 1.24   | 0.71              |
| 6.82                              | 2.19                                 | 8.53   | 3.42                                 | 10.3   | 5.10                                 | 12.4   | 7.28                                 | 1.11   | 0.75              |
| 7.39                              | 2.12                                 | 9.25   | 3.32                                 | 11.2   | 4.87                                 | 13.5   | 7.09                                 | 0.975  | 0.80              |
| 7.97                              | 2.05                                 | 9.99   | 3.23                                 | 12.1   | 4.73                                 | 14.6   | 6.92                                 | 0.864  | 0.85              |
| 8.57                              | 2.00                                 | 10.7   | 3.14                                 | 13.0   | 4.61                                 | 15.8   | 6.77                                 | 0.770  | 0.90              |
| 9.17                              | 1.95                                 | 11.5   | 3.07                                 | 13.9   | 4.50                                 | 16.9   | 6.62                                 | 0.691  | 0.95              |
| 9.78                              | 1.90                                 | 12.3   | 3.00                                 | 14.9   | 4.40                                 | 18.1   | 6.50                                 | 0.624  | 1.00              |
| 11.0                              | 1.82                                 | 13.9   | 2.88                                 | 16.8   | 4.22                                 | 20.5   | 6.27                                 | 0.516  | (1.10)            |
| 11.3                              | 1.80                                 | 14.2   | 2.86                                 | 17.2   | 4.19                                 | 21.0   | 6.22                                 | 0.497  | 1.12              |
| 12.3                              | 1.75                                 | 15.5   | 2.78                                 | 18.8   | 4.07                                 | 23.0   | 6.07                                 | 0.433  | (1.20)            |
| 13.0                              | 1.72                                 | 16.4   | 2.73                                 | 19.8   | 4.00                                 | 24.3   | 5.98                                 | 0.399  | 1.25              |
| 15.0                              | 1.63                                 | 19.0   | 2.61                                 | 23.0   | 3.82                                 | 28.2   | 5.74                                 | 0.318  | 1.40              |
| 16.4                              | 1.59                                 | 20.8   | 2.54                                 | 25.2   | 3.72                                 | 30.9   | 5.61                                 | 0.277  | 1.50              |
| 17.9                              | 1.55                                 | 22.6   | 2.47                                 | 27.4   | 3.63                                 | 33.7   | 5.49                                 | 0.244  | 1.60              |
| 20.8                              | 1.48                                 | 26.4   | 2.37                                 | 32.0   | 3.47                                 | 39.4   | 5.28                                 | 0.193  | 1.80              |
| 23.9                              | 1.42                                 | 30.3   | 2.28                                 | 36.7   | 3.34                                 | 45.4   | 5.11                                 | 0.156  | 2.00              |
| 27.1                              | 1.37                                 | 34.4   | 2.21                                 | 41.7   | 3.23                                 | 51.6   | 4.96                                 | 0.129  | (2.20)            |
| 27.8                              | 1.36                                 | 35.2   | 2.19                                 | 42.7   | 3.21                                 | 52.9   | 4.94                                 | 0.124  | 2.24              |
| 32.1                              | 1.31                                 | 40.8   | 2.11                                 | 49.4   | 3.10                                 | 61.4   | 4.78                                 | 0.0998   | 2.50              |
| 37.4                              | 1.26                                 | 47.5   | 2.04                                 | 57.4   | 2.99                                 | 71.6   | 4.63                                 | 0.0796   | 2.80              |
| 41.0                              | 1.23                                 | 52.1   | 1.99                                 | 63.1   | 2.93                                 | 78.6   | 4.54                                 | 0.0693   | 3.00              |
| 43.7                              | 1.21                                 | 55.6   | 1.97                                 | 67.4   | 2.88                                 | 84.1   | 4.49                                 | 0.0629   | 3.15              |
| 44.7                              | 1.21                                 | 56.8   | 1.96                                 | 68.8   | 2.87                                 | 85.9   | 4.47                                 | 0.0609   | (3.20)            |
| 50.4                              | 1.18                                 | 64.2   | 1.91                                 | 77.7   | 2.79                                 | 97.1   | 4.37                                 | 0.0509   | (3.50)            |
| 51.4                              | 1.17                                 | 65.4   | 1.90                                 | 79.2   | 2.78                                 | 99.1   | 4.35                                 | 0.0495   | 3.55              |
| 60.4                              | 1.13                                 | 76.9   | 1.84                                 | 93.2   | 2.69                                 | 117    | 4.23                                 | 0.0390   | 4.00              |
| 71.0                              | 1.10                                 | 90.4   | 1.78                                 | 109    | 2.61                                 | 137    | 4.11                                 | 0.0308   | 4.50              |
| 82.0                              | 1.07                                 | 104    | 1.73                                 | 127    | 2.54                                 | 159    | 4.02                                 | 0.0249   | 5.00              |
| 93.7                              | 1.05                                 | 119    | 1.69                                 | 144    | 2.48                                 | 182    | 3.94                                 | 0.0206   | 5.50              |
| 95.9                              | 1.04                                 | 122    | 1.69                                 | 148    | 2.47                                 | 186    | 3.92                                 | 0.0199   | 5.60              |
| 105                               | 1.02                                 | 134    | 1.60                                 | 163    | 2.44                                 | 205    | 3.87                                 | 0.0173   | 6.00              |
| 113                               | 1.01                                 | 144    | 1.64                                 | 174    | 2.41                                 | 220    | 3.83                                 | 0.0157   | 6.30              |

In the following some examples are given:

**Example 1**

Question:

What current is required to increase the temperature by 200 °C of ISA® 13 wire with a diameter of 0.20 mm?

Solution:

- a) From the table can be seen that the value for ISOTAN® wire with equal diameter is 1.03 A.
- b) This value must be converted for ISA® 13 in accordance with the previously quoted formula; this results in

$$i_x = 1.03 \cdot \sqrt{\frac{49}{13.3}} = \frac{1.03 \cdot 1.92}{\approx 2 \text{ A}}$$

where 49 is the resistivity of ISOTAN® in μΩ x cm and 13.3 the resistivity of ISA® 13 in μΩ x cm, at 200 °C, respectively.

Result:

An ISA®13 wire with a diameter of 0.20 mm must be loaded with a current of 2 A in order to increase its temperature by 200 °C.

**Example 2**

Question:

What is the temperature increase of ISA®-CHROM 60 wire with a diameter of 1.0 mm, if it is loaded with a current of 8 A?

Solution:

- a) In accordance with the previously quoted formula, for 20 °C the conversion factor for ISA®-CHROM 60 alloy is calculated to be

$$\sqrt{\frac{49}{111^1)} = 0.664$$

- b) In order to get the load value for ISOTAN® wire with equal diameter, the value for ISA®-CHROM 60 must be divided by this value, thus

$$i_{\text{ISOTAN}} = \frac{8 \text{ Amps}}{0.664} = 12 \text{ A}$$

This results in a value of 12 A for ISOTAN® alloy.

If an ISOTAN® wire of equal diameter is loaded with the calculated 12 A, its temperature will increase by somewhat less than 400 °C.

As can be seen from the table on page 67, an overtemperature of 400 °C is achieved by applying a current of 12.3 A.

The conversion factor determined as per a) applies to 20 °C; it must now be re-determined for 400 °C. It is 0.644, resulting from

$$\sqrt{\frac{49}{118^1)}$$

where 0.49 is the resistivity of ISOTAN® in μΩ x cm and 1.18 that of ISA®-CHROM 60 in μΩ x cm, at 400 °C, respectively.

Now if the load current of 8 A for ISA®-CHROM 60 at 400 °C is re-calculated for ISOTAN®, a value of 12.4 A for ISOTAN® wire with equal diameter will result. Since for 400 °C a value of 12.3 A applies, you will get the following:

Result:

If an ISA®-CHROM 60 wire with a diameter of 1.0 mm is loaded with a current of 8 A, its temperature will increase by somewhat more than 400 °C.

<sup>1)</sup> These values apply to a state after rapid cooling.

### Current-Carrying Capacity of Flat Wires

For round wires the diameter is sufficient to determine the data previously quoted. For ribbons the thickness and above all, the width must be taken into consideration.

When making comparisons, the table containing the cross-sectional values of standard ribbons with rounded-off edges vs. those of round wires should be consulted.

At high temperature (600 °C) or if for other reasons the proportion of heat dissipation by radiation exceeds the dissipation by convection, flat wires and ribbons of any dimension have a current-carrying capacity greater than that of round wires with an equal cross-sectional area, due to their larger surface area.

In case of the heat dissipation taking place mainly by convection - generally at low temperatures -, the current carrying capacity of flat wires and ribbons will exceed that of flat wires of an equal cross-sectional area only for ratios between width and thickness of more than 15 : 1.

If flat wires are wound onto a carrier there will be a larger contact area available for heat transfer to the carrier by heat conductance as compared with round wires, but no generally valid data can be given as to a possibly higher current-carrying capacity. For heat dissipation to the outside, of course, only a part, i. e. one half of the surface of the ribbon is available; this must be kept in mind when making calculations.

The following tables give information on the resistance, surface and weight of flat ISOTAN® wires, referenced at 1 m. In addition they contain data as to the load currents for ribbons of ISOTAN® at overtemperatures of 100/200/300 and 400 °C.

The following should be mentioned:

Since the edges are rounded-off, the cross-sectional area and resistance of flat wires are calculated by the formula below.

The factor 0.215 refers to the optimal cross section with an edge rounding being equal to an optimal semicircle. As this is not a matter of fact, the real geometry may deviate from the calculated value.

### Calculation of the Cross-Sectional Area and Resistance of Flat Wires

$$R = \frac{\rho \cdot l \cdot 10^{-3}}{a(b - a \cdot 0.215)}$$

$$S = a(b - a \cdot 0.215)$$

$$O = [a(\pi - 2) + 2b] \cdot l$$

**a** = Thickness in mm

**b** = Width in mm

**l** = Length in mm

**R** = Resistance in Ω

**S** = Cross-sectional area in mm<sup>2</sup>

**O** = Surface in mm<sup>2</sup>

**ρ** = Resistivity in Ω · mm · m<sup>-1</sup>

The values in the current-carrying capacity tables refer to bare wire or bare ribbon. Oxidized wire and ribbon can, due to improved heat dissipation, withstand a load increase of up to 20 %, expressed in Watt per cm<sup>2</sup>.

The current-carrying capacity of ribbons of other alloys can be calculated with the same method as described for wires.

### Diameter of Round Wires of Equal Cross-Sectional Area in mm

| Thickness<br>a in mm | Width / b in mm |      |      |      |      |      |      |      |      |      |
|----------------------|-----------------|------|------|------|------|------|------|------|------|------|
|                      | 1               | 2    | 3    | 4    | 5    | 6    | 7    | 8    | 9    | 10   |
| 0.05                 | 0.25            | 0.36 | 0.44 | 0.50 | 0.56 | 0.62 | 0.67 | 0.71 | 0.76 | 0.80 |
| 0.06                 | 0.27            | 0.39 | 0.48 | 0.55 | 0.62 | 0.68 | 0.73 | 0.78 | 0.83 | 0.87 |
| 0.07                 | 0.30            | 0.42 | 0.52 | 0.60 | 0.67 | 0.73 | 0.79 | 0.84 | 0.89 | 0.94 |
| 0.08                 | 0.32            | 0.45 | 0.55 | 0.64 | 0.71 | 0.78 | 0.84 | 0.90 | 0.96 | 1.01 |
| 0.09                 | 0.34            | 0.48 | 0.58 | 0.68 | 0.76 | 0.83 | 0.89 | 0.96 | 1.01 | 1.07 |
| 0.10                 | 0.35            | 0.50 | 0.62 | 0.71 | 0.80 | 0.87 | 0.94 | 1.01 | 1.07 | 1.13 |
| 0.12                 | 0.39            | 0.55 | 0.67 | 0.78 | 0.87 | 0.96 | 1.03 | 1.10 | 1.17 | 1.23 |
| 0.14                 | 0.42            | 0.59 | 0.73 | 0.84 | 0.94 | 1.03 | 1.11 | 1.19 | 1.26 | 1.33 |
| 0.16                 | 0.44            | 0.63 | 0.78 | 0.90 | 1.01 | 1.10 | 1.19 | 1.27 | 1.35 | 1.42 |
| 0.18                 | 0.47            | 0.67 | 0.82 | 0.95 | 1.07 | 1.17 | 1.26 | 1.35 | 1.43 | 1.51 |
| 0.20                 | 0.49            | 0.71 | 0.87 | 1.00 | 1.12 | 1.23 | 1.33 | 1.42 | 1.51 | 1.59 |
| 0.22                 | 0.52            | 0.74 | 0.91 | 1.05 | 1.18 | 1.29 | 1.40 | 1.49 | 1.58 | 1.67 |
| 0.24                 | 0.54            | 0.77 | 0.95 | 1.10 | 1.23 | 1.35 | 1.46 | 1.56 | 1.65 | 1.74 |
| 0.26                 | 0.56            | 0.80 | 0.99 | 1.14 | 1.28 | 1.40 | 1.52 | 1.62 | 1.72 | 1.81 |
| 0.28                 | 0.58            | 0.83 | 1.02 | 1.19 | 1.33 | 1.46 | 1.57 | 1.68 | 1.79 | 1.88 |
| 0.30                 | 0.60            | 0.86 | 1.06 | 1.23 | 1.37 | 1.51 | 1.63 | 1.74 | 1.85 | 1.95 |
| 0.35                 | 0.64            | 0.93 | 1.14 | 1.32 | 1.48 | 1.62 | 1.76 | 1.88 | 1.99 | 2.10 |
| 0.40                 | 0.68            | 0.99 | 1.22 | 1.41 | 1.58 | 1.74 | 1.88 | 2.01 | 2.13 | 2.25 |
| 0.45                 | 0.72            | 1.04 | 1.29 | 1.50 | 1.68 | 1.84 | 1.99 | 2.13 | 2.26 | 2.38 |
| 0.50                 | 0.75            | 1.10 | 1.36 | 1.57 | 1.76 | 1.94 | 2.09 | 2.24 | 2.38 | 2.51 |
| 0.60                 |                 | 1.20 | 1.48 | 1.72 | 1.93 | 2.12 | 2.29 | 2.45 | 2.60 | 2.75 |
| 0.70                 |                 | 1.28 | 1.59 | 1.85 | 2.08 | 2.28 | 2.47 | 2.64 | 2.81 | 2.96 |
| 0.80                 |                 | 1.36 | 1.70 | 1.97 | 2.22 | 2.44 | 2.64 | 2.82 | 3.00 | 3.16 |
| 0.90                 |                 | 1.44 | 1.79 | 2.09 | 2.35 | 2.58 | 2.79 | 2.99 | 3.18 | 3.35 |
| 1.00                 |                 | 1.51 | 1.88 | 2.20 | 2.47 | 2.71 | 2.94 | 3.15 | 3.34 | 3.53 |
| 1.20                 |                 |      | 2.05 | 2.39 | 2.69 | 2.96 | 3.21 | 3.44 | 3.65 | 3.86 |
| 1.40                 |                 |      | 2.19 | 2.57 | 2.89 | 3.19 | 3.46 | 3.70 | 3.94 | 4.16 |
| 1.60                 |                 |      | 2.33 | 2.73 | 3.08 | 3.39 | 3.68 | 3.95 | 4.20 | 4.44 |
| 1.80                 |                 |      | 2.45 | 2.88 | 3.25 | 3.59 | 3.89 | 4.18 | 4.44 | 4.69 |
| 2.00                 |                 |      | 2.56 | 3.02 | 3.41 | 3.77 | 4.09 | 4.39 | 4.67 | 4.94 |

Surface of Flat Wires in  $\text{cm}^2 \cdot \text{m}^{-1}$

| Thickness<br>a in mm | Width / b in mm |      |      |      |      |      |      |      |      |      |
|----------------------|-----------------|------|------|------|------|------|------|------|------|------|
|                      | 1               | 2    | 3    | 4    | 5    | 6    | 7    | 8    | 9    | 10   |
| 0.05                 | 0.44            | 0.89 | 1.3  | 1.8  | 2.2  | 2.7  | 3.1  | 3.6  | 4.0  | 4.4  |
| 0.06                 | 0.53            | 1.1  | 1.6  | 2.1  | 2.7  | 3.2  | 3.7  | 4.3  | 4.8  | 5.3  |
| 0.07                 | 0.61            | 1.2  | 1.9  | 2.5  | 3.1  | 3.7  | 4.4  | 5.0  | 5.6  | 6.2  |
| 0.08                 | 0.70            | 1.4  | 2.1  | 2.8  | 3.5  | 4.3  | 5.0  | 5.7  | 6.4  | 7.1  |
| 0.09                 | 0.79            | 1.6  | 2.4  | 3.2  | 4.0  | 4.8  | 5.6  | 6.4  | 7.2  | 8.0  |
| 0.10                 | 0.87            | 1.8  | 2.7  | 3.5  | 4.4  | 5.3  | 6.2  | 7.1  | 8.0  | 8.9  |
| 0.12                 | 1.0             | 2.1  | 3.2  | 4.2  | 5.3  | 6.4  | 7.4  | 8.5  | 9.6  | 10.7 |
| 0.14                 | 1.2             | 2.5  | 3.7  | 4.9  | 6.2  | 7.4  | 8.7  | 9.9  | 11.2 | 12.4 |
| 0.16                 | 1.4             | 2.8  | 4.2  | 5.6  | 7.1  | 8.5  | 9.9  | 11.3 | 12.8 | 14.2 |
| 0.18                 | 1.5             | 3.1  | 4.7  | 6.3  | 7.9  | 9.6  | 11.2 | 12.8 | 14.4 | 16.0 |
| 0.20                 | 1.7             | 3.5  | 5.3  | 7.0  | 8.8  | 10.6 | 12.4 | 14.2 | 15.9 | 17.7 |
| 0.22                 | 1.9             | 3.8  | 5.8  | 7.7  | 9.7  | 11.7 | 13.6 | 15.6 | 17.5 | 19.5 |
| 0.24                 | 2.0             | 4.2  | 6.3  | 8.4  | 10.6 | 12.7 | 14.8 | 17.0 | 19.1 | 21.2 |
| 0.26                 | 2.2             | 4.5  | 6.8  | 9.1  | 11.4 | 13.8 | 16.1 | 18.4 | 20.7 | 23.0 |
| 0.28                 | 2.3             | 4.8  | 7.3  | 9.8  | 12.3 | 14.8 | 17.3 | 19.8 | 22.3 | 24.8 |
| 0.30                 | 2.5             | 5.2  | 7.8  | 10.5 | 13.2 | 15.8 | 18.5 | 21.2 | 23.9 | 26.5 |
| 0.35                 | 2.9             | 6.0  | 9.1  | 12.2 | 15.3 | 18.5 | 21.6 | 24.7 | 27.8 | 30.9 |
| 0.40                 | 3.3             | 6.8  | 10.4 | 13.9 | 17.5 | 21.1 | 24.6 | 28.2 | 31.7 | 35.3 |
| 0.45                 | 3.6             | 7.6  | 11.6 | 15.6 | 19.6 | 23.6 | 27.6 | 31.7 | 35.7 | 39.7 |
| 0.50                 | 4.0             | 8.4  | 12.9 | 17.3 | 21.8 | 26.2 | 30.7 | 35.1 | 39.6 | 44.0 |
| 0.60                 |                 | 10.0 | 15.3 | 20.7 | 26.0 | 31.4 | 36.7 | 42.0 | 47.4 | 52.7 |
| 0.70                 |                 | 11.5 | 17.8 | 24.0 | 30.2 | 36.4 | 42.7 | 48.9 | 55.1 | 61.4 |
| 0.80                 |                 | 13.0 | 20.1 | 27.3 | 34.4 | 41.5 | 48.6 | 55.7 | 62.9 | 70.0 |
| 0.90                 |                 | 14.5 | 22.5 | 30.5 | 38.5 | 46.5 | 54.5 | 62.5 | 70.5 | 78.6 |
| 1.00                 |                 | 15.9 | 24.8 | 33.7 | 42.6 | 51.5 | 60.4 | 69.3 | 78.2 | 87.1 |
| 1.20                 |                 |      | 29.3 | 40.0 | 50.6 | 61.3 | 72.0 | 82.7 | 93.4 | 104  |
| 1.40                 |                 |      | 33.6 | 46.1 | 58.5 | 71.0 | 83.5 | 95.9 | 108  | 121  |
| 1.60                 |                 |      | 37.8 | 52.1 | 66.3 | 80.5 | 94.8 | 109  | 123  | 138  |
| 1.80                 |                 |      | 41.9 | 57.9 | 73.9 | 89.9 | 106  | 122  | 138  | 154  |
| 2.00                 |                 |      | 45.7 | 63.5 | 81.3 | 99.1 | 117  | 135  | 153  | 170  |

Flat Wires of ISOTAN® - Grams per Meter ( $\text{g} \cdot \text{m}^{-1}$ )

| Thickness<br>a in mm | Width / b in mm |      |      |      |     |     |     |     |     |     |
|----------------------|-----------------|------|------|------|-----|-----|-----|-----|-----|-----|
|                      | 1               | 2    | 3    | 4    | 5   | 6   | 7   | 8   | 9   | 10  |
| 0.05                 | 20.6            | 40.6 | 60.6 | 80.6 | 101 | 121 | 141 | 161 | 181 | 201 |
| 0.06                 | 20.7            | 40.7 | 60.7 | 80.7 | 101 | 121 | 141 | 161 | 181 | 201 |
| 0.07                 | 20.8            | 40.8 | 60.8 | 80.8 | 101 | 121 | 141 | 161 | 181 | 201 |
| 0.08                 | 20.9            | 40.9 | 60.9 | 80.9 | 101 | 121 | 141 | 161 | 181 | 201 |
| 0.09                 | 21.0            | 41.0 | 61.0 | 81.0 | 101 | 121 | 141 | 161 | 181 | 201 |
| 0.10                 | 21.1            | 41.1 | 61.1 | 81.1 | 101 | 121 | 141 | 161 | 181 | 201 |
| 0.12                 | 21.4            | 41.4 | 61.4 | 81.4 | 101 | 121 | 141 | 161 | 181 | 201 |
| 0.14                 | 21.6            | 41.6 | 61.6 | 81.6 | 102 | 122 | 142 | 162 | 182 | 202 |
| 0.16                 | 21.8            | 41.8 | 61.8 | 81.8 | 102 | 122 | 142 | 162 | 182 | 202 |
| 0.18                 | 22.1            | 42.1 | 62.1 | 82.1 | 102 | 122 | 142 | 162 | 182 | 202 |
| 0.20                 | 22.3            | 42.3 | 62.3 | 82.3 | 102 | 122 | 142 | 162 | 182 | 202 |
| 0.22                 | 22.5            | 42.5 | 62.5 | 82.5 | 103 | 123 | 143 | 163 | 183 | 203 |
| 0.24                 | 22.7            | 42.7 | 62.7 | 82.7 | 103 | 123 | 143 | 163 | 183 | 203 |
| 0.26                 | 23.0            | 43.0 | 63.0 | 83.0 | 103 | 123 | 143 | 163 | 183 | 203 |
| 0.28                 | 23.2            | 43.2 | 63.2 | 83.2 | 103 | 123 | 143 | 163 | 183 | 203 |
| 0.30                 | 23.4            | 43.4 | 63.4 | 83.4 | 103 | 123 | 143 | 163 | 183 | 203 |
| 0.35                 | 24.0            | 44.0 | 64.0 | 84.0 | 104 | 124 | 144 | 164 | 184 | 204 |
| 0.40                 | 24.6            | 44.6 | 64.6 | 84.6 | 105 | 125 | 145 | 165 | 185 | 205 |
| 0.45                 | 25.1            | 45.1 | 65.1 | 85.1 | 105 | 125 | 145 | 165 | 185 | 205 |
| 0.50                 | 25.7            | 45.7 | 65.7 | 85.7 | 106 | 126 | 146 | 166 | 186 | 206 |
| 0.60                 |                 | 46.8 | 66.8 | 86.8 | 107 | 127 | 147 | 167 | 187 | 207 |
| 0.70                 |                 | 48.0 | 68.0 | 88.0 | 108 | 128 | 148 | 168 | 188 | 208 |
| 0.80                 |                 | 49.1 | 69.1 | 89.1 | 109 | 129 | 149 | 169 | 189 | 209 |
| 0.90                 |                 | 50.3 | 70.3 | 90.3 | 110 | 130 | 150 | 170 | 190 | 210 |
| 1.00                 |                 | 51.4 | 71.4 | 91.4 | 111 | 131 | 151 | 171 | 191 | 211 |
| 1.20                 |                 |      | 73.7 | 93.7 | 114 | 134 | 154 | 174 | 194 | 214 |
| 1.40                 |                 |      | 76.0 | 96.0 | 116 | 136 | 156 | 176 | 196 | 216 |
| 1.60                 |                 |      | 78.3 | 98.3 | 118 | 138 | 158 | 178 | 198 | 218 |
| 1.80                 |                 |      | 80.5 | 101  | 121 | 141 | 161 | 181 | 201 | 221 |
| 2.00                 |                 |      | 82.8 | 103  | 123 | 143 | 163 | 183 | 203 | 223 |

**Current-Carrying Capacity of Flat Wires of ISOTAN®**  
**in Ampere for an Overtemperature of 100 °C**  
 Horizontally stretched in still air of 20 °C

| Thickness<br>a in mm | Width / b in mm |      |      |      |      |      |      |      |      |      |
|----------------------|-----------------|------|------|------|------|------|------|------|------|------|
|                      | 1               | 2    | 3    | 4    | 5    | 6    | 7    | 8    | 9    | 10   |
| 0.05                 | 0.93            | 1.60 | 2.13 | 2.66 | 3.20 | 3.64 | 4.12 | 4.56 | 5.03 | 5.51 |
| 0.06                 | 1.02            | 1.75 | 2.33 | 2.91 | 3.50 | 3.98 | 4.50 | 4.99 | 5.51 | 6.03 |
| 0.07                 | 1.10            | 1.89 | 2.52 | 3.15 | 3.78 | 4.31 | 4.87 | 5.40 | 5.96 | 6.52 |
| 0.08                 | 1.17            | 2.02 | 2.69 | 3.36 | 4.04 | 4.60 | 5.20 | 5.77 | 6.36 | 6.96 |
| 0.09                 | 1.25            | 2.14 | 2.85 | 3.56 | 4.28 | 4.88 | 5.51 | 6.11 | 6.74 | 7.38 |
| 0.10                 | 1.31            | 2.25 | 3.00 | 3.75 | 4.51 | 5.14 | 5.80 | 6.43 | 7.10 | 7.77 |
| 0.12                 | 1.44            | 2.45 | 3.29 | 4.11 | 4.94 | 5.63 | 6.35 | 7.04 | 7.78 | 8.51 |
| 0.14                 | 1.55            | 2.67 | 3.55 | 4.44 | 5.34 | 6.08 | 6.87 | 7.61 | 8.41 | 9.20 |
| 0.16                 | 1.66            | 2.85 | 3.80 | 4.75 | 5.71 | 6.50 | 7.35 | 8.14 | 9.00 | 9.84 |
| 0.18                 | 1.76            | 3.02 | 4.03 | 5.04 | 6.05 | 6.89 | 7.79 | 8.63 | 9.53 | 10.4 |
| 0.20                 | 1.85            | 3.19 | 4.25 | 5.31 | 6.38 | 7.27 | 8.22 | 9.10 | 10.0 | 11.0 |
| 0.22                 | 1.95            | 3.34 | 4.46 | 5.57 | 6.70 | 7.63 | 8.62 | 9.55 | 10.5 | 11.5 |
| 0.24                 | 2.03            | 3.49 | 4.66 | 5.82 | 7.00 | 7.97 | 9.00 | 10.0 | 11.0 | 12.0 |
| 0.26                 | 2.12            | 3.64 | 4.84 | 6.06 | 7.28 | 8.29 | 9.37 | 10.4 | 11.5 | 12.5 |
| 0.28                 | 2.20            | 3.77 | 5.03 | 6.28 | 7.55 | 8.60 | 9.72 | 10.8 | 11.9 | 13.0 |
| 0.30                 | 2.27            | 3.91 | 5.21 | 6.51 | 7.82 | 8.91 | 10.1 | 11.2 | 12.3 | 13.5 |
| 0.35                 | 2.46            | 4.22 | 5.62 | 7.03 | 8.45 | 9.63 | 10.9 | 12.1 | 13.3 | 14.6 |
| 0.40                 | 2.62            | 4.51 | 6.00 | 7.51 | 9.02 | 10.3 | 11.6 | 12.9 | 14.2 | 15.5 |
| 0.45                 | 2.78            | 4.78 | 6.37 | 7.97 | 9.58 | 10.9 | 12.3 | 13.7 | 15.1 | 16.5 |
| 0.50                 | 2.93            | 5.04 | 6.72 | 8.40 | 10.1 | 11.5 | 13.0 | 14.4 | 15.9 | 17.4 |
| 0.60                 |                 | 5.52 | 7.36 | 9.21 | 11.1 | 12.6 | 14.2 | 15.8 | 17.4 | 19.1 |
| 0.70                 |                 | 5.97 | 7.95 | 9.94 | 12.0 | 13.6 | 15.4 | 17.0 | 18.8 | 20.6 |
| 0.80                 |                 | 6.37 | 8.49 | 10.6 | 12.8 | 14.5 | 16.4 | 18.2 | 20.1 | 22.0 |
| 0.90                 |                 | 6.77 | 9.02 | 11.3 | 13.6 | 15.4 | 17.4 | 19.3 | 21.3 | 23.3 |
| 1.00                 |                 | 7.13 | 9.50 | 11.9 | 14.3 | 16.3 | 18.4 | 20.4 | 22.5 | 24.6 |
| 1.20                 |                 |      | 10.4 | 12.9 | 15.6 | 17.7 | 20.0 | 22.2 | 24.5 | 26.8 |
| 1.40                 |                 |      | 11.2 | 14.0 | 16.9 | 19.2 | 21.7 | 24.0 | 26.5 | 29.0 |
| 1.60                 |                 |      | 12.0 | 15.0 | 18.0 | 20.5 | 23.2 | 25.7 | 28.3 | 31.0 |
| 1.80                 |                 |      | 12.8 | 15.9 | 19.1 | 21.8 | 24.6 | 27.3 | 30.1 | 33.0 |
| 2.00                 |                 |      | 13.5 | 16.8 | 20.1 | 22.9 | 25.9 | 28.7 | 31.7 | 34.7 |

**Current-Carrying Capacity of Flat Wires of ISOTAN®**  
**in Ampere for an Overtemperature of 200 °C**  
 Horizontally stretched in still air of 20 °C

| Thickness<br>a in mm | Width / b in mm |       |      |      |       |      |      |      |      |      |
|----------------------|-----------------|-------|------|------|-------|------|------|------|------|------|
|                      | 1               | 2     | 3    | 4    | 5     | 6    | 7    | 8    | 9    | 10   |
| 0.05                 | 1.40            | 2.26  | 3.11 | 3.94 | 4.75  | 5.53 | 6.29 | 7.06 | 7.86 | 8.60 |
| 0.06                 | 1.53            | 2.47  | 3.41 | 4.31 | 5.19  | 6.05 | 6.88 | 7.72 | 8.60 | 9.38 |
| 0.07                 | 1.66            | 2.68  | 3.68 | 4.66 | 5.62  | 6.55 | 7.45 | 8.35 | 9.30 | 10.1 |
| 0.08                 | 1.77            | 2.86  | 3.93 | 4.98 | 6.00  | 7.00 | 7.95 | 8.91 | 9.93 | 10.8 |
| 0.09                 | 1.88            | 3.03  | 4.17 | 5.28 | 6.36  | 7.41 | 8.43 | 9.45 | 10.5 | 11.5 |
| 0.10                 | 1.98            | 3.19  | 4.39 | 5.56 | 6.70  | 7.81 | 8.88 | 9.95 | 11.1 | 12.1 |
| 0.12                 | 2.17            | 3.49  | 4.81 | 6.09 | 7.34  | 8.55 | 9.72 | 10.9 | 12.1 | 13.3 |
| 0.14                 | 2.34            | 3.78  | 5.20 | 6.58 | 7.93  | 9.24 | 10.5 | 11.8 | 13.1 | 14.3 |
| 0.16                 | 2.50            | 4.04  | 5.56 | 7.04 | 8.48  | 9.88 | 11.2 | 12.6 | 14.0 | 15.3 |
| 0.18                 | 2.65            | 4.28  | 5.89 | 7.46 | 8.99  | 10.5 | 11.9 | 13.4 | 14.9 | 16.2 |
| 0.20                 | 2.80            | 4.51  | 6.21 | 7.87 | 9.48  | 11.0 | 12.6 | 14.1 | 15.7 | 17.1 |
| 0.22                 | 2.94            | 4.74  | 6.52 | 8.25 | 9.94  | 11.6 | 13.2 | 14.8 | 16.5 | 18.0 |
| 0.24                 | 3.07            | 4.95  | 6.81 | 8.62 | 10.40 | 12.1 | 13.8 | 15.4 | 17.2 | 18.8 |
| 0.26                 | 3.19            | 5.15  | 7.09 | 8.98 | 10.8  | 12.6 | 14.3 | 16.1 | 17.9 | 19.5 |
| 0.28                 | 3.31            | 5.34  | 7.35 | 9.31 | 11.2  | 13.1 | 14.9 | 16.7 | 18.6 | 20.3 |
| 0.30                 | 3.43            | 5.53  | 7.62 | 9.64 | 11.6  | 13.5 | 15.4 | 17.3 | 19.2 | 21.0 |
| 0.35                 | 3.71            | 5.98  | 8.23 | 10.4 | 12.6  | 14.6 | 16.6 | 18.6 | 20.7 | 22.7 |
| 0.40                 | 3.96            | 6.38  | 8.78 | 11.1 | 13.4  | 15.6 | 17.8 | 19.9 | 22.2 | 24.2 |
| 0.45                 | 4.20            | 6.78  | 9.33 | 11.8 | 14.2  | 16.6 | 18.9 | 21.1 | 23.6 | 25.7 |
| 0.50                 | 4.43            | 7.17  | 9.85 | 12.4 | 15.0  | 17.5 | 19.9 | 22.3 | 24.8 | 27.1 |
| 0.60                 |                 | 7.75  | 10.8 | 13.6 | 16.4  | 19.1 | 21.8 | 24.4 | 27.2 | 29.7 |
| 0.70                 |                 | 8.45  | 11.6 | 14.7 | 17.7  | 20.8 | 23.5 | 26.4 | 29.4 | 32.1 |
| 0.80                 |                 | 9.03  | 12.4 | 15.7 | 19.0  | 22.1 | 25.1 | 28.2 | 31.4 | 34.2 |
| 0.90                 |                 | 9.58  | 13.2 | 16.7 | 20.1  | 23.4 | 26.7 | 29.9 | 33.3 | 36.3 |
| 1.00                 |                 | 10.10 | 13.9 | 17.6 | 21.2  | 24.7 | 28.1 | 31.5 | 35.1 | 38.3 |
| 1.20                 |                 |       | 15.2 | 19.2 | 23.1  | 26.9 | 30.6 | 34.3 | 38.3 | 41.7 |
| 1.40                 |                 |       | 16.4 | 20.8 | 25.0  | 29.1 | 33.2 | 37.2 | 41.4 | 45.2 |
| 1.60                 |                 |       | 17.5 | 22.2 | 26.7  | 31.1 | 35.4 | 39.7 | 44.2 | 48.3 |
| 1.80                 |                 |       | 18.6 | 23.6 | 28.4  | 33.1 | 37.7 | 42.2 | 47.0 | 51.3 |
| 2.00                 |                 |       | 19.6 | 24.8 | 29.9  | 34.8 | 39.6 | 44.4 | 49.5 | 54.0 |

**Current-Carrying Capacity of Flat Wires of ISOTAN®**  
**in Ampere for an Overtemperature of 300 °C**  
 Horizontally stretched in still air of 20 °C

| Thickness<br>a in mm | Width / b in mm |      |      |      |      |      |      |      |      |      |
|----------------------|-----------------|------|------|------|------|------|------|------|------|------|
|                      | 1               | 2    | 3    | 4    | 5    | 6    | 7    | 8    | 9    | 10   |
| 0.05                 | 1.94            | 3.09 | 4.19 | 5.33 | 6.43 | 7.55 | 8.62 | 9.70 | 10.7 | 11.8 |
| 0.06                 | 2.12            | 3.38 | 4.58 | 5.83 | 7.03 | 8.26 | 9.43 | 10.6 | 11.7 | 12.9 |
| 0.07                 | 2.29            | 3.66 | 4.96 | 6.31 | 7.61 | 8.93 | 10.2 | 11.5 | 12.7 | 13.9 |
| 0.08                 | 2.45            | 3.91 | 5.29 | 6.73 | 8.12 | 9.54 | 10.9 | 12.3 | 13.5 | 14.9 |
| 0.09                 | 2.59            | 4.14 | 5.61 | 7.14 | 8.61 | 10.1 | 11.6 | 13.0 | 14.3 | 15.8 |
| 0.10                 | 2.73            | 4.36 | 5.91 | 7.52 | 9.07 | 10.6 | 12.2 | 13.7 | 15.1 | 16.6 |
| 0.12                 | 2.99            | 4.77 | 6.47 | 8.24 | 9.93 | 11.7 | 13.3 | 15.0 | 16.5 | 18.1 |
| 0.14                 | 3.23            | 5.16 | 7.00 | 8.90 | 10.7 | 12.6 | 14.4 | 16.2 | 17.9 | 19.6 |
| 0.16                 | 3.46            | 5.52 | 7.48 | 9.52 | 11.5 | 13.5 | 15.4 | 17.3 | 19.1 | 21.0 |
| 0.18                 | 3.66            | 5.85 | 7.93 | 10.1 | 12.2 | 14.3 | 16.3 | 18.4 | 20.3 | 22.3 |
| 0.20                 | 3.86            | 6.17 | 8.36 | 10.6 | 12.8 | 15.1 | 17.2 | 19.4 | 21.4 | 23.5 |
| 0.22                 | 4.05            | 6.47 | 8.77 | 11.2 | 13.5 | 15.8 | 18.1 | 20.3 | 22.4 | 24.6 |
| 0.24                 | 4.23            | 6.76 | 9.16 | 11.7 | 14.1 | 16.5 | 18.9 | 21.2 | 23.4 | 25.7 |
| 0.26                 | 4.41            | 7.04 | 9.54 | 12.1 | 14.6 | 17.2 | 19.6 | 22.1 | 24.4 | 26.8 |
| 0.28                 | 4.57            | 7.30 | 9.89 | 12.6 | 15.2 | 17.8 | 20.4 | 22.9 | 25.3 | 27.8 |
| 0.30                 | 4.73            | 7.56 | 10.2 | 13.0 | 15.7 | 18.5 | 21.1 | 23.7 | 26.2 | 28.8 |
| 0.35                 | 5.11            | 8.17 | 11.1 | 14.1 | 17.0 | 20.0 | 22.8 | 25.6 | 28.3 | 31.3 |
| 0.40                 | 5.46            | 8.72 | 11.8 | 15.0 | 18.1 | 21.3 | 24.3 | 27.4 | 30.2 | 33.2 |
| 0.45                 | 5.80            | 9.26 | 12.5 | 15.9 | 19.3 | 22.6 | 25.8 | 29.1 | 32.1 | 35.2 |
| 0.50                 | 6.11            | 9.72 | 13.2 | 16.8 | 20.3 | 23.8 | 27.2 | 30.6 | 33.8 | 37.1 |
| 0.60                 |                 | 10.7 | 14.5 | 18.4 | 22.2 | 26.1 | 29.8 | 33.6 | 37.2 | 40.7 |
| 0.70                 |                 | 11.6 | 15.7 | 19.9 | 24.0 | 28.2 | 32.2 | 36.2 | 40.0 | 43.9 |
| 0.80                 |                 | 12.3 | 16.7 | 21.3 | 25.7 | 30.1 | 34.4 | 38.7 | 42.7 | 46.9 |
| 0.90                 |                 | 13.1 | 17.7 | 22.6 | 27.2 | 32.0 | 36.5 | 41.1 | 45.4 | 49.8 |
| 1.00                 |                 | 13.8 | 18.7 | 23.8 | 28.7 | 33.7 | 38.5 | 43.3 | 47.8 | 52.5 |
| 1.20                 |                 |      | 20.4 | 25.9 | 31.3 | 36.7 | 42.0 | 47.2 | 52.1 | 57.2 |
| 1.40                 |                 |      | 22.1 | 28.1 | 33.9 | 39.8 | 45.5 | 51.1 | 56.4 | 61.9 |
| 1.60                 |                 |      | 23.6 | 30.0 | 36.2 | 42.5 | 48.5 | 54.6 | 60.2 | 66.1 |
| 1.80                 |                 |      | 25.1 | 31.9 | 38.5 | 45.2 | 51.6 | 58.0 | 64.1 | 70.3 |
| 2.00                 |                 |      | 26.4 | 33.6 | 40.5 | 47.5 | 54.3 | 61.1 | 67.4 | 74.0 |

**Current-Carrying Capacity of Flat Wires of ISOTAN®**  
**in Ampere for an Overtemperature of 400 °C**  
 Horizontally stretched in still air of 20 °C

| Thickness<br>a in mm | Width / b in mm |      |      |      |      |      |      |      |      |      |
|----------------------|-----------------|------|------|------|------|------|------|------|------|------|
|                      | 1               | 2    | 3    | 4    | 5    | 6    | 7    | 8    | 9    | 10   |
| 0.05                 | 2.44            | 3.88 | 5.29 | 6.66 | 8.09 | 9.50 | 10.9 | 12.3 | 13.6 | 15.0 |
| 0.06                 | 2.67            | 4.24 | 5.78 | 7.30 | 8.84 | 10.4 | 11.9 | 13.4 | 14.9 | 16.4 |
| 0.07                 | 2.89            | 4.58 | 6.25 | 7.90 | 9.57 | 11.2 | 12.9 | 14.5 | 16.1 | 17.7 |
| 0.08                 | 3.08            | 4.90 | 6.68 | 8.43 | 10.2 | 12.0 | 13.8 | 15.5 | 17.2 | 18.9 |
| 0.09                 | 3.27            | 5.19 | 7.08 | 8.94 | 10.8 | 12.7 | 14.6 | 16.4 | 18.2 | 20.0 |
| 0.10                 | 3.44            | 5.47 | 7.46 | 9.42 | 11.4 | 13.4 | 15.4 | 17.3 | 19.2 | 21.1 |
| 0.12                 | 3.77            | 5.98 | 8.17 | 10.3 | 12.5 | 14.7 | 16.8 | 18.9 | 21.0 | 23.1 |
| 0.14                 | 4.08            | 6.47 | 8.83 | 11.1 | 13.5 | 15.9 | 18.2 | 20.5 | 22.7 | 25.0 |
| 0.16                 | 4.36            | 6.92 | 9.47 | 11.9 | 14.4 | 17.0 | 19.4 | 21.9 | 24.3 | 26.7 |
| 0.18                 | 4.62            | 7.34 | 10.0 | 12.6 | 15.3 | 18.0 | 20.6 | 23.3 | 25.8 | 28.3 |
| 0.20                 | 4.87            | 7.73 | 10.5 | 13.3 | 16.1 | 19.0 | 21.7 | 24.5 | 27.2 | 29.9 |
| 0.22                 | 5.11            | 8.11 | 11.1 | 14.0 | 16.9 | 19.9 | 22.8 | 25.7 | 28.5 | 31.3 |
| 0.24                 | 5.34            | 8.48 | 11.6 | 14.6 | 17.7 | 20.8 | 23.8 | 26.8 | 29.8 | 32.7 |
| 0.26                 | 5.56            | 8.82 | 12.0 | 15.2 | 18.4 | 21.6 | 24.8 | 27.9 | 31.0 | 34.1 |
| 0.28                 | 5.77            | 9.15 | 12.5 | 15.8 | 19.1 | 22.4 | 25.7 | 28.9 | 32.2 | 35.4 |
| 0.30                 | 5.97            | 9.48 | 12.9 | 16.3 | 19.8 | 23.2 | 26.6 | 30.0 | 33.3 | 36.6 |
| 0.35                 | 6.45            | 10.2 | 14.0 | 17.6 | 21.4 | 25.1 | 28.8 | 32.4 | 36.0 | 39.5 |
| 0.40                 | 6.89            | 10.9 | 14.9 | 18.8 | 22.8 | 26.8 | 30.7 | 34.6 | 38.4 | 42.2 |
| 0.45                 | 7.31            | 11.6 | 15.8 | 20.0 | 24.2 | 28.5 | 32.6 | 36.7 | 40.8 | 44.8 |
| 0.50                 | 7.69            | 12.2 | 16.7 | 21.1 | 25.5 | 30.0 | 34.4 | 38.7 | 43.0 | 47.2 |
| 0.60                 |                 | 13.4 | 18.3 | 23.1 | 28.0 | 32.9 | 37.7 | 42.4 | 47.1 | 51.8 |
| 0.70                 |                 | 14.5 | 19.6 | 24.9 | 30.2 | 35.5 | 40.7 | 45.8 | 50.9 | 55.9 |
| 0.80                 |                 | 15.5 | 21.1 | 26.6 | 32.3 | 37.9 | 43.4 | 48.9 | 54.4 | 59.7 |
| 0.90                 |                 | 16.4 | 22.4 | 28.3 | 34.3 | 40.2 | 46.1 | 51.9 | 57.7 | 63.4 |
| 1.00                 |                 | 17.3 | 23.6 | 29.8 | 36.1 | 42.4 | 48.6 | 54.7 | 60.8 | 66.8 |
| 1.20                 |                 |      | 25.7 | 32.5 | 39.3 | 46.2 | 53.0 | 59.6 | 66.3 | 72.8 |
| 1.40                 |                 |      | 27.8 | 35.2 | 42.6 | 50.0 | 57.3 | 64.5 | 71.7 | 78.8 |
| 1.60                 |                 |      | 29.7 | 37.5 | 45.5 | 53.4 | 61.2 | 68.9 | 76.6 | 84.2 |
| 1.80                 |                 |      | 31.6 | 40.0 | 48.4 | 56.8 | 65.1 | 73.3 | 81.5 | 89.5 |
| 2.00                 |                 |      | 33.3 | 42.0 | 50.9 | 59.8 | 68.5 | 77.1 | 85.7 | 94.2 |

# D. Technical Terms of Delivery and Tolerances

## Available Types

Our alloys are available in the form of


- annealed bare wires; on request ISOTAN®, ISA®-CHROM 60 and ISA®-CHROM 80 can be manufactured with an insulating oxide film;
- ML-enamel
- solderable enamel (polyurethane), heat resistant up to 150 °C
- heat resistant enamel (polyimide), not solderable, up to 200 °C
- enamelled wires with or without synthetic (rayon) or silk or glass fibre cover;
- annealed flat wires with round-off edges (calculation of cross-sectional area see page 69);
- annealed ribbons, also in sheet or panel form;
- foils;
- stranded wires;
- rods, drawn and straightened, also forged rods.

On request our alloys can also be delivered with special values of hardness resp. tensile strength.

## Dimensional Range


- Bare wires 0.01 – 10 mm Ø
- Insulated wires 0.01 – 2 mm Ø
- Flat wires 0.05 – 2 mm Ø
- Metal sheets and panels 0.10 – 10 mm Ø
- Foils 0.005– 0.10 mm

The dimensional ranges are illustrated in the following diagram; details are given on request.



### Packing

Wires of less than 1 mm Ø and flat wires of less than 0.80 mm thickness and a maximum width of 5 mm are delivered on plastic spools according to DIN IEC 264 resp. on American standard spools in accordance with the tables on the right.




**Insulated wires** are delivered on plastic spools as for bare wires.

**Stranded wires** are delivered on special spools holding up to 100 kg per spool in one length.

**Ribbon** with a maximum width of 10 mm can be delivered on special spools; ribbon of more than 10 mm width is delivered spirally wound in the form of disks with an inner diameter of 100 mm and an outer diameter of 300 mm maximum.

**Wires** with a diameter of more than 1 mm can be delivered on spools or wound in coils as per the table on the right.

### Reels for Tapes, Tubes and Cables



### Spools According to DIN IEC 264

| Spool Dimensions (mm) |                |                |                |                | Weight of Wound-Up Wire<br>kg appr. | On Plastic Spools<br>Round Wires up to 1.0 mm Ø<br>Flat Wires up to<br>5.0 mm Width and 0.8 mm Thickness |                  |                  |                  |
|-----------------------|----------------|----------------|----------------|----------------|-------------------------------------|--|------------------|------------------|------------------|
| Spool Diameter        |                |                | Spool Width    |                |                                     | ≤ 0.10   | > 0.10<br>≤ 0.40 | > 0.40<br>≤ 0.70 | > 0.70<br>≤ 1.00 |
| d <sub>1</sub>        | d <sub>2</sub> | d <sub>3</sub> | l <sub>1</sub> | l <sub>2</sub> |                                     |  |                  |                  |                  |
| 50                    | 32             | 11             | 50             | 38             | 0.1                                 | +  |                  |                  |                  |
| 63                    | 40             | 11             | 63             | 49             | 0.4                                 | +  |                  |                  |                  |
| 80                    | 50             | 16             | 80             | 64             | 0.7                                 | +  | +                |                  |                  |
| 100                   | 63             | 16             | 100            | 80             | 1.5                                 |  | +                |                  |                  |
| 125                   | 80             | 16             | 125            | 100            | 3.0                                 |  | +                | +                |                  |
| 160                   | 100            | 22             | 160            | 128            | 7.0                                 |  | +                | +                |                  |
| 200                   | 125            | 22             | 200            | 160            | 13.0                                |  | +                | +                |                  |
| 250                   | 160            | 22             | 200            | 160            | 23.0                                |  | +                | +                |                  |
| 355                   | 224            | 36             | 200            | 160            | 45.0                                |  |                  | +                |                  |
| 500                   | 315            | 36             | 250            | 180            | 80.0                                |  |                  | +                |                  |

### American Spools

|    |      |    |    |    |      |                              |
|----|------|----|----|----|------|------------------------------|
| 63 | 44.3 | 16 | 61 | 51 | 0.25 | Designation 060 „Half-Cut“   |
| 63 | 44.3 | 16 | 86 | 76 | 0.45 | Designation 065 „1 lb Spool“ |

### Special Spool

for wires > 0.8 mm Ø with reference to DIN IEC 264

|     |     |     |     |     |     |          |
|-----|-----|-----|-----|-----|-----|----------|
| 560 | 315 | 127 | 400 | 300 | 200 | > 0.8 mm |
|-----|-----|-----|-----|-----|-----|----------|

### Special Spool with Conical Flanges for Finest Sizes

outer dimensions correspond to the American „half-cut“ –spool.

### Spool with Conical Flanges

in accordance with DIN EN 60264-5-1; to be agreed upon.

### Coils

| Round Wires > 1mm Ø               |                                      |                                      | Flat Wires > 5.0 mm Width<br>> 0.8 mm Thickness |  |
|-----------------------------------|--------------------------------------|--------------------------------------|---|--|
| Wire Diameter resp.<br>Width (mm) | Inner Diameter of Coil<br>(mm) appr. | Outer Diameter of Coil<br>(mm) appr. | Weight of Coil (kg) appr.                       |  |
| > 1.0 - 2.5                       | 300                                  | 400                                  | 20  |  |
| > 2.5 - 6.0                       | 550                                  | 700                                  | 60  |  |

### Materials:

PS = high impact polystyrene

ABS = Acrylonitrile Butadiene Styrene

PE = Polyethylene

Other materials and further information on request.

### Packaging:

On request.

### Remarks:

All measures, weights and loads indicated are approximate figures. Tolerances and deviations as usual in the trade.

Dimensions in mm, all dimensions are nominal dimensions.

| Illustration on the left (below) |     |    |    |    |      | Weight in g                       |     |    |                                |
|----------------------------------|-----|----|----|----|------|-----------------------------------|-----|----|--------------------------------|
| Type                             | d1  | d2 | d3 | L1 | L2   | Winding volume in cm <sup>3</sup> |     |    |                                |
|                                  |     |    |    |    |      | possible materials                |     |    |                                |
|                                  |     |    |    |    |      | remarks                           |     |    |                                |
| MP250                            | 250 | 60 | 20 | 30 | 0-15 | 410                               | 693 | PS | L 2 variable by sliding flange |

### Technical Terms of Delivery

For bare wires the terms of delivery of DIN 46460, part 1, apply; dimensions and resistance values are standardized in DIN 46461 and 46463. In general for linear resistance a tolerance of  $\pm 5\%$  from the nominal value applies; this may increase to  $\pm 10\%$  maximum for thin wires and low resistance alloys. Within one wire length the tolerance is approx.  $\pm 1\%$  maximum from the actual resistance per meter. For oxidized wires the technical terms of delivery are summarized in DIN 46464.

Wires insulated by an oxide layer can be used at temperatures up to the maximum working temperature for bare wires. The break-down voltage is more than 10 V for ISOTAN<sup>®</sup> and more than 3 V for the nickel-chromium alloys ISA<sup>®</sup>-CHROM 80 and ISA<sup>®</sup>-CHROM 60.

For enamelled and silk-covered wires the terms of delivery of DIN 46460, Parts 2 - 4, and DIN 46462 apply.

Enamelled wires are treated with a so-called solderable enamel (DIN designation Type V); the wires may be directly tinned if the alloys permit. On request a high-temperature resistant enamel (DIN designation Type W 200), usable at temperatures of up to 200 °C, or even more for short periods, is available.

The break-down voltage for both types ranges from 700 to more than 2500 V, depending on the diameter.

The wires can also be covered with rayon, natural silk or glass fibre. Subsequent impregnation with silicone varnish for improved adhesion is possible. The break-down voltage is several hundred volts.

For certain applications, especially if insulated wires are used for heating bimetals, a combination of several insulation types is recommended.

Flat wires of resistance alloys are standardized in DIN 46465. It should be noted that the nominal dimensions quoted there often will not meet the requirements of our customers and that for this reason we have chosen a different gradation.

For resistance alloys supplied as ribbon or sheet, no special standard exists. Here we apply the permissible values stated in DIN 13599 (DIN 1791) for copper and wrought copper alloys, as regards thickness and width tolerances.

For stranded wires of resistance alloys, too, no special standards exist. The technical terms of delivery must be negotiated individually. If stranded wires are used for heating cables, however, the regulations of VDE 0253 must be observed.

On request special tolerance values can be offered.

### Dimensions in mm

| Nominal Diameter<br>d1 | Increase of Diameter<br>d2 - d1 |       | Outer Diameter of Enamelled Wire<br>d2 |       |       |       |
|------------------------|---------------------------------|-------|--|-------|-------|-------|
|                        | L                               | 2L    | min.                                   | max.  | min.  | max.  |
| 0.020                  | 0.005                           | 0.009 | 0.023                                  | 0.029 | 0.027 | 0.036 |
| 0.025                  | 0.006                           | 0.010 | 0.029                                  | 0.036 | 0.033 | 0.042 |
| 0.030                  | 0.006                           | 0.011 | 0.034                                  | 0.042 | 0.039 | 0.048 |
| 0.040                  | 0.007                           | 0.012 | 0.045                                  | 0.053 | 0.050 | 0.060 |
| 0.045                  | 0.008                           | 0.013 | 0.051                                  | 0.059 | 0.056 | 0.066 |
| 0.050                  | 0.008                           | 0.014 | 0.056                                  | 0.064 | 0.062 | 0.072 |
| 0.060                  | 0.009                           | 0.016 | 0.067                                  | 0.076 | 0.074 | 0.084 |
| 0.071                  | 0.010                           | 0.017 | 0.079                                  | 0.089 | 0.086 | 0.097 |
| 0.080                  | 0.011                           | 0.018 | 0.088                                  | 0.099 | 0.095 | 0.108 |
| 0.090                  | 0.012                           | 0.019 | 0.098                                  | 0.111 | 0.106 | 0.120 |
| 0.100                  | 0.012                           | 0.021 | 0.109                                  | 0.122 | 0.117 | 0.123 |
| 0.125                  | 0.014                           | 0.023 | 0.136                                  | 0.150 | 0.145 | 0.161 |
| 0.140                  | 0.015                           | 0.024 | 0.151                                  | 0.166 | 0.160 | 0.179 |
| 0.150                  | 0.016                           | 0.025 | 0.162                                  | 0.177 | 0.171 | 0.191 |
| 0.160                  | 0.017                           | 0.026 | 0.173                                  | 0.188 | 0.182 | 0.202 |
| 0.180                  | 0.018                           | 0.028 | 0.193                                  | 0.210 | 0.203 | 0.225 |
| 0.200                  | 0.019                           | 0.030 | 0.214                                  | 0.231 | 0.225 | 0.248 |
| 0.250                  | 0.022                           | 0.034 | 0.266                                  | 0.285 | 0.278 | 0.304 |
| 0.280                  | 0.024                           | 0.036 | 0.297                                  | 0.318 | 0.309 | 0.338 |
| 0.300                  | 0.025                           | 0.037 | 0.318                                  | 0.339 | 0.330 | 0.360 |
| 0.400                  | 0.028                           | 0.043 | 0.418                                  | 0.445 | 0.433 | 0.468 |
| 0.450                  | 0.030                           | 0.046 | 0.469                                  | 0.498 | 0.485 | 0.524 |
| 0.500                  | 0.031                           | 0.049 | 0.519                                  | 0.551 | 0.537 | 0.578 |
| 0.600                  | 0.035                           | 0.054 | 0.620                                  | 0.657 | 0.639 | 0.686 |
| 0.800                  | 0.041                           | 0.062 | 0.821                                  | 0.869 | 0.842 | 0.902 |
| 0.900                  | 0.043                           | 0.066 | 0.921                                  | 0.973 | 0.944 | 1.010 |
| 1.000                  | 0.046                           | 0.070 | 1.021                                  | 1.079 | 1.045 | 1.117 |
| 1.250                  | 0.053                           | 0.080 | 1.271                                  | 1.343 | 1.298 | 1.387 |
| 1.400                  | 0.056                           | 0.085 | 1.421                                  | 1.499 | 1.450 | 1.548 |
| 1.500                  | 0.059                           | 0.090 | 1.521                                  | 1.605 | 1.552 | 1.654 |

Special sizes: to be agreed upon.

# E. Corrosion Resistance

At room temperature the alloys manufactured by us exhibit good corrosion resistance in the bare condition. In order to avoid corrosion during storage, it is recommended that the environment should be as dry as possible.

Alloys with a high copper content have a tendency to surface corrosion after long periods of storage.

It should be kept in mind that oxidized wires of nickel-chromium alloys can be destroyed when stored in a moist environment. The alloy MANGANIN® is susceptible to stress crack corrosion; it also requires to be stored at a dry place.

The corrosion resistance characteristics at maximum working temperature can be seen from the table on the right.

On completion of soldering, brazing or welding work the flux must be removed very thoroughly, since it can contribute to corrosion, especially at higher temperatures.

| Designation   | Corrosion Resistant up to Maximum Working Temperature against |                                       |  |                          |           | Carburization |        |        |
|---------------|---|---------------------------------------|--|--------------------------|-----------|---------------|--------|--------|
|               | Atmospheric Corrosion at 20 °C                                | Air and Other Oxygen Containing Gases | Nitrogen Containing Gases with Little Oxygen Content | Sulphur-Containing Gases |           |               |        |        |
|               |   |                                       |  | Oxidizing                | Reductive |               |        |        |
| ISAOHM®       | high  | high                                  | high   | high                     | high      | high          |        |        |
| ISA®-CHROM 60 |   |                                       |  | medium                   | medium    |               | medium | medium |
| ISA®-CHROM 80 |   |                                       |  |                          |           |               |        |        |
| ISA®-CHROM 30 |   |                                       |  |                          |           |               |        |        |
| ISOTAN®       |   |                                       |  | medium                   | medium    |               | medium | medium |
| ISA-NICKEL®   |   |                                       |  |                          |           |               |        |        |
| MANGANIN®     |   |                                       |  |                          |           |               |        |        |
| NICKELIN-W    |   | high                                  | high   | high                     | high      |               |        |        |
| RESISTHERM®   |   |                                       |  |                          |           |               |        |        |
| ISA®-ZIN      |   |                                       |  |                          |           |               |        |        |
| ZERANIN® 30   |   | medium                                | medium   | medium                   | low       |               |        |        |
| ALLOY 127     |   |                                       |  |                          |           |               |        |        |
| ALLOY 90      |   |                                       |  |                          |           |               |        |        |
| ISA® 13       |   | low                                   | low  | low                      | low       |               |        |        |
| ALLOY 60      |   |                                       |  |                          |           |               |        |        |
| NICKEL        |   |                                       |  |                          |           |               |        |        |
| ALLOY 30      | high  | high                                  | high   | high                     |           |               |        |        |
| CUNI1         |   |                                       |  |                          |           |               |        |        |
| E-COPPER      |   |                                       |  |                          |           |               |        |        |
|               | medium  | low                                   | low  | low                      | low       |               |        |        |

# F. Instructions for Treatment

The alloys delivered by Isabellenhütte have good working characteristics.

The following instructions should be observed:

## Winding

All wires should be treated as carefully as possible, with a tension below the yield point. The yield point can be taken as being appr. 50 % below tensile strength in annealed condition.

## Aging

Even when winding a resistance wire with little tension deformation can take place. By simple bending, mechanical stresses are built up in the wire. They affect the electrical resistance and should be minimized by heat treatment.

Copper alloys can increase their resistivity by deformation; for ISOTAN® e. g. this increase can achieve up to 7 %. As regards nickel-chromium alloys, deformation reduces the resistivity, for ISAOHM® e. g. up to 10 %.

Heat treatment – which is also called artificial aging – is especially required when precision resistors are manufactured.

Aging is a stabilization process; it can be accelerated considerably by applying temperatures well above ambient temperatures. The size of the aging temperature is determined by the material and especially by the insulation used.

In some cases artificial aging by

temperature cycling is an advantage. Here temperature cycles between 20 °C and maximum aging temperature are repeatedly run.

The aging temperature should not exceed 140 °C because of the sensitivity to heat of the wire insulation. Bare wires slightly begin to oxidize above 100 °C; this oxide layer can be removed by pickling.

## Pickling

The type of pickling bath is mainly determined by the nature of the alloy. For MANGANIN® e. g. sulphuric chromic acid, for ZERANIN® 30 nitric acid, for ISOTAN® also nitric acid or persulphate pickle is used; for nickel-chromium alloys pickling in phosphoric acid has proven its value. The immersion period lasts for 1 to 10 minutes depending on the alloy.

## Soldering, Brazing and Welding of Resistance Alloys

### Soldering

The copper alloys manufactured by Isabellenhütte can be soldered like pure copper, using normal solders and fluxes. Light abrasion of the areas to be soldered is recommended.

When soldering precision resistors a leadfree solder (e. g. L-SnAg5 according to DIN 1707) and only acid-free fluxes (preferably pure colophony) should be used. Even the smallest residual of aggressive fluxes causes corrosion of the wire and thus alteration to the resistance. Solders containing lead may be subject to metallic alterations.

The melting point of the solder must be such as to prevent softening over time. In general, however, brazing should be preferred.

When soldering precision resistors spot-soldering is recommended. The very high temperature coefficient of the electric resistance of tin (pure tin = 4600 ppm/K) affects also the temperature coefficient of the resistance material.

ISAOHM® alloy can only be soldered by using particularly aggressive fluxes, as used for soldering stainless steels (e. g. Soldaflux Z by Degussa). In addition, the surfaces must be roughened beforehand. But even then the bond does not have the quality as with copper alloys.

In all cases the flux must be carefully removed.

### Brazing

The soundest and most reliable bonds are made by brazing. Since the temperature coefficient and resistivity of the alloys for precision resistors are affected by heating, it is recommended to use low melting point brazing solders (L-Ag40Cd DIN 1707, e. g. "Degussa 4003") and to keep the brazing time as short as possible. Flux "h" of Degussa has proved useful.

### Welding

The alloys can be welded, especially spot and butt welded. It must be kept in mind, however, that the electrical and heat conductivities as well as the melting points often greatly differ from the respective values of other materials.

### General

Besides those mentioned above normally no other peculiarities need to be taken into consideration.

### **Cutting**

While with copper-nickel alloys no problems arise, nickel-chromium alloys and pure nickel are tough and show high strength at high temperatures; they thus tend to "weld together" with the tools.

This must be taken into consideration when drilling, threading or sawing. Under certain circumstances it may be more favourable to use hard, i. e. unannealed, alloys.



# G. Conversion Tables

## Resistivity

|                                     | $\Omega$ /sq mil ft | $\Omega$ /CMF | $\mu\Omega$ /cub | $\Omega \cdot \text{mm}^2/\text{m}$ | $\mu\Omega \cdot \text{cm}$ |
|-------------------------------------|---------------------|---------------|------------------|-------------------------------------|-----------------------------|
| $\Omega$ /sq mil ft                 | 1                   | 1.273         | 0.08333          | 0.0021167                           | 0.21167                     |
| $\Omega$ /cir mil ft                | 0.7854              | 1             | 0.0654           | 0.0016624                           | 0.16624                     |
| $\mu\Omega$ /cub                    | 12                  | 15.279        | 1                | 0.0254                              | 2.54                        |
| $\Omega \cdot \text{mm}^2/\text{m}$ | 472.44              | 601.54        | 39.37            | 1                                   | 100                         |
| $\mu\Omega \cdot \text{cm}$         | 4.7244              | 6.0154        | 0.3937           | 0.01                                | 1                           |

$\Omega$  - CMF: CMF = circular mil foot

The length of the wire is measured in feet.

The area is measured in *circular mil* and a *mil* is one thousandth of an inch.

A circular mil is the area of a circle with a diameter of 1 mil.

$$1 \Omega \cdot \text{CMF} = 0.1662 \times 10^{-8} \Omega \cdot \text{m}$$

$$1 \Omega \cdot \text{CMF} = 0.1662 \times 10^{-6} \Omega \cdot \text{cm}$$

$$1 \Omega \cdot \text{CMF} = 0.1662 \mu\Omega \cdot \text{cm}$$

## Electrical Resistance

|                | $\Omega$ /ft | $\Omega$ /yard | $\Omega$ /m |
|----------------|--------------|----------------|-------------|
| $\Omega$ /ft   | 1            | 3              | 3.281       |
| $\Omega$ /yard | 0.3333       | 1              | 1.094       |
| $\Omega$ /m    | 0.3048       | 0.9144         | 1           |

## Units of Length

|      | inch   | foot   | yard   | mm    | m      |
|------|--------|--------|--------|-------|--------|
| inch | 1      | 0.0833 | 0.0278 | 25.4  | 0.0254 |
| foot | 12     | 1      | 0.3333 | 304.8 | 0.3048 |
| yard | 36     | 3      | 1      | 914.4 | 0.9144 |
| mm   | 0.0394 | 0.0033 | -      | 1     | 0.001  |
| m    | 39.37  | 3.281  | 1.094  | 1000  | 1      |

## Units of Surface Area

|                 | square inch | square foot | square yard | $\text{mm}^2$ | $\text{m}^2$ |
|-----------------|-------------|-------------|-------------|---------------|--------------|
| 1 square inch   | 1           | -           | -           | 645.2         | -            |
| 1 square foot   | 144         | 1           | 0.1111      | 92900         | 0.0929       |
| 1 square yard   | 1296        | 9           | 1           | -             | 0.8361       |
| 1 $\text{mm}^2$ | 0.0016      | -           | -           | 1             | $10^{-6}$    |
| 1 $\text{m}^2$  | 1550        | 10.76       | 1.196       | $10^6$        | 1            |

## Units of Space

|                 | cubic inch | cubic foot | cubic yard | $\text{cm}^3$ | $\text{dm}^3$ |
|-----------------|------------|------------|------------|---------------|---------------|
| 1 cubic inch    | 1          | -          | -          | 16.39         | 0.0164        |
| 1 cubic foot    | 1728       | 1          | 0.037      | -             | 28.32         |
| 1 cubic yard    | 46656      | 27         | 1          | -             | 764.6         |
| 1 $\text{cm}^3$ | 0.061      | -          | -          | 1             | 0.001         |
| 1 $\text{dm}^3$ | 61.02      | 0.035      | -          | 1000          | 1             |

## Units of Weight

|                          | oz     | lb     | g     | kg     |
|--------------------------|--------|--------|-------|--------|
| ounce (oz) <sup>1)</sup> | 1      | 0.0625 | 28.35 | 0.028  |
| pound (lb)               | 16     | 1      | 453.6 | 0.4536 |
| gram (g)                 | 0.0353 | -      | 1     | 0.001  |
| kilogram (kg)            | 35.274 | 2.2046 | 1000  | 1      |

<sup>1)</sup> 1 troy ounce corresponds to 31.1035 g

## Density

|                        | lb/cub in | $\text{g}/\text{cm}^3$ |
|------------------------|-----------|------------------------|
| lb/cub in              | 1         | 27.68                  |
| $\text{g}/\text{cm}^3$ | 0.03613   | 1                      |

## Strength

|                   | psi    | Kp/ $\text{mm}^2$ | MPa    |
|-------------------|--------|-------------------|--------|
| psi               | 1      | 0.0007021         | 0.0069 |
| Kp/ $\text{mm}^2$ | 1422.3 | 1                 | 9.81   |
| MPa*              | 145    | 0.102             | 1      |

\*) 1 MPa = 1 N/ $\text{mm}^2$

### Conversion of Units of the Coefficient of Thermal Conductivity ( $\lambda$ )

| Units of $\lambda$              | $\frac{W}{m K}$      | $\frac{W}{cm K}$   | $\frac{kcal}{cm s \text{ grd}}$ | $\frac{J}{cm s K}$ | $\frac{kpm}{cm s \text{ grd}}$ |
|---------------------------------|----------------------|--------------------|---------------------------------|--------------------|--------------------------------|
| $\frac{W}{m K}$                 | 1                    | $10^{-2}$          | $2.39 \cdot 10^{-6}$            | $10^{-2}$          | $1.02 \cdot 10^{-3}$           |
| $\frac{W}{cm K}$                | $10^2$               | 1                  | $2.39 \cdot 10^{-4}$            | 1                  | 0.102                          |
| $\frac{kcal}{cm s \text{ grd}}$ | $0.419 \cdot 10^6$   | $4.187 \cdot 10^3$ | 1                               | $4.187 \cdot 10^3$ | $4.27 \cdot 10^2$              |
| $\frac{J}{cm s K}$              | 100                  | 1                  | $2.39 \cdot 10^{-4}$            | 1                  | 0.102                          |
| $\frac{kpm}{cm s \text{ grd}}$  | $9.80665 \cdot 10^2$ | 9.81               | $2.39 \cdot 10^{-3}$            | 9.81               | 1                              |

$\lambda$  = Coefficient of thermal conductivity, heat or thermal conductivity, thermal conductance

$$\lambda = \frac{Q\Delta l}{A\Delta t}$$

### Conversion of Units of Work, Energy (W), Thermal Energy (Q)

| Units of Work, Energy (W)<br>Thermal Energy (Q) | Joule<br>J                  | Kilowatt-Hour<br>kWh   | Horse-Power-Hour<br>PSh | Kilopond-Meter<br>kpm | Kilogram-Calorie<br>kcal |
|---|-----------------------------|------------------------|-------------------------|-----------------------|--------------------------|
| Joule J<br>= Watt-Second/Ws<br>= Nm             | 1                           | $0.2778 \cdot 10^{-6}$ | $0.3774 \cdot 10^{-6}$  | 0.102                 | $0.2388 \cdot 10^{-3}$   |
| Kilowatt-Hour<br>kWh                            | $3.6 \cdot 10^6$            | 1                      | 1.359                   | $0.367 \cdot 10^6$    | $0.86 \cdot 10^3$        |
| Horse-Power-Hour<br>PSh                         | $2.65 \cdot 10^6$           | 0.736                  | 1                       | $0.2702 \cdot 10^6$   | $0.6329 \cdot 10^3$      |
| Kilopond-Meter<br>kpm                           | $9.80665$<br>$\approx 9.81$ | $2.724 \cdot 10^{-6}$  | $3.702 \cdot 10^{-6}$   | 1                     | $2.342 \cdot 10^{-3}$    |
| Kilogram-Calorie<br>kcal                        | $4.187 \cdot 10^3$          | $1.163 \cdot 10^{-3}$  | $1.58 \cdot 10^{-3}$    | $0.427 \cdot 10^3$    | 1                        |

### Conversion mm/Inches

| mm   | Inches | mm   | Inches | mm   | Inches |
|------|--------|------|--------|------|--------|
| 0.01 | 0.0004 | 0.45 | 0.0177 | 0.89 | 0.0350 |
| 0.02 | 0.0008 | 0.46 | 0.0181 | 0.90 | 0.0354 |
| 0.03 | 0.0012 | 0.47 | 0.0185 | 0.91 | 0.0358 |
| 0.04 | 0.0016 | 0.48 | 0.0189 | 0.92 | 0.0362 |
| 0.05 | 0.0020 | 0.49 | 0.0193 | 0.93 | 0.0366 |
| 0.06 | 0.0024 | 0.50 | 0.0197 | 0.94 | 0.0370 |
| 0.07 | 0.0028 | 0.51 | 0.0201 | 0.95 | 0.0374 |
| 0.08 | 0.0031 | 0.52 | 0.0205 | 0.96 | 0.0378 |
| 0.09 | 0.0035 | 0.53 | 0.0209 | 0.97 | 0.0382 |
| 0.10 | 0.0039 | 0.54 | 0.0213 | 0.98 | 0.0386 |
| 0.11 | 0.0043 | 0.55 | 0.0217 | 0.99 | 0.0390 |
| 0.12 | 0.0047 | 0.56 | 0.0220 | 1    | 0.0394 |
| 0.13 | 0.0051 | 0.57 | 0.0224 | 2    | 0.0787 |
| 0.14 | 0.0055 | 0.58 | 0.0228 | 3    | 0.1181 |
| 0.15 | 0.0059 | 0.59 | 0.0232 | 4    | 0.1575 |
| 0.16 | 0.0063 | 0.60 | 0.0236 | 5    | 0.1969 |
| 0.17 | 0.0067 | 0.61 | 0.0240 | 6    | 0.2362 |
| 0.18 | 0.0071 | 0.62 | 0.0244 | 7    | 0.2756 |
| 0.19 | 0.0075 | 0.63 | 0.0248 | 8    | 0.3150 |
| 0.20 | 0.0079 | 0.64 | 0.0252 | 9    | 0.3543 |
| 0.21 | 0.0083 | 0.65 | 0.0256 | 10   | 0.3937 |
| 0.22 | 0.0087 | 0.66 | 0.0260 | 11   | 0.4331 |
| 0.23 | 0.0091 | 0.67 | 0.0264 | 12   | 0.4724 |
| 0.24 | 0.0094 | 0.68 | 0.0268 | 13   | 0.5118 |
| 0.25 | 0.0098 | 0.69 | 0.0272 | 14   | 0.5512 |
| 0.26 | 0.0102 | 0.70 | 0.0276 | 15   | 0.5906 |
| 0.27 | 0.0106 | 0.71 | 0.0280 | 16   | 0.6299 |
| 0.28 | 0.0110 | 0.72 | 0.0283 | 17   | 0.6693 |
| 0.29 | 0.0114 | 0.73 | 0.0287 | 18   | 0.7087 |
| 0.30 | 0.0118 | 0.74 | 0.0291 | 19   | 0.7480 |
| 0.31 | 0.0122 | 0.75 | 0.0295 | 20   | 0.7874 |
| 0.32 | 0.0126 | 0.76 | 0.0299 | 21   | 0.8268 |
| 0.33 | 0.0130 | 0.77 | 0.0303 | 22   | 0.8661 |
| 0.34 | 0.0134 | 0.78 | 0.0307 | 23   | 0.9055 |
| 0.35 | 0.0138 | 0.79 | 0.0311 | 24   | 0.9449 |
| 0.36 | 0.0142 | 0.80 | 0.0315 | 25   | 0.9843 |
| 0.37 | 0.0146 | 0.81 | 0.0319 | 26   | 1.0236 |
| 0.38 | 0.0150 | 0.82 | 0.0323 | 27   | 1.0630 |
| 0.39 | 0.0154 | 0.83 | 0.0327 | 28   | 1.1024 |
| 0.40 | 0.0157 | 0.84 | 0.0331 | 29   | 1.1417 |
| 0.41 | 0.0161 | 0.85 | 0.0335 | 30   | 1.1811 |
| 0.42 | 0.0165 | 0.86 | 0.0339 | 31   | 1.2205 |
| 0.43 | 0.0169 | 0.87 | 0.0343 | 32   | 1.2598 |
| 0.44 | 0.0173 | 0.88 | 0.0346 | 33   | 1.2992 |

### Wire Gauges

| Gauge | S.W.G  |         | B & S/A.W.G. |        | Gauge |
|-------|--------|---------|--------------|--------|-------|
|       | Inches | mm      | Inches       | mm     |       |
| 6-0   | 0.464  | 11.7856 | -            | -      | 6-0   |
| 5-0   | 0.432  | 10.9728 | -            | -      | 5-0   |
| 4-0   | 0.4    | 10.1600 | 0.460        | 11.68  | 4-0   |
| 3-0   | 0.372  | 9.4488  | 0.41         | 10.41  | 3-0   |
| 2-0   | 0.348  | 8.8392  | 0.365        | 9.27   | 2-0   |
| 0     | 0.324  | 8.2296  | 0.325        | 8.26   | 0     |
| 1     | 0.3    | 7.6200  | 0.289        | 7.34   | 1     |
| 2     | 0.276  | 7.0104  | 0.258        | 6.55   | 2     |
| 3     | 0.252  | 6.4008  | 0.229        | 5.82   | 3     |
| 4     | 0.232  | 5.8928  | 0.204        | 5.18   | 4     |
| 5     | 0.212  | 5.3848  | 0.182        | 4.62   | 5     |
| 6     | 0.192  | 4.8768  | 0.162        | 4.11   | 6     |
| 7     | 0.176  | 4.4704  | 0.144        | 3.66   | 7     |
| 8     | 0.16   | 4.0640  | 0.129        | 3.28   | 8     |
| 9     | 0.144  | 3.6576  | 0.114        | 2.90   | 9     |
| 10    | 0.128  | 3.2512  | 0.102        | 2.59   | 10    |
| 11    | 0.116  | 2.9464  | 0.0907       | 2.30   | 11    |
| 12    | 0.104  | 2.6416  | 0.0808       | 2.05   | 12    |
| 13    | 0.092  | 2.3368  | 0.0720       | 1.83   | 13    |
| 14    | 0.08   | 2.0320  | 0.0641       | 1.63   | 14    |
| 15    | 0.072  | 1.8288  | 0.0571       | 1.45   | 15    |
| 16    | 0.064  | 1.6256  | 0.0508       | 1.29   | 16    |
| 17    | 0.056  | 1.4224  | 0.0453       | 1.15   | 17    |
| 18    | 0.048  | 1.2192  | 0.0403       | 1.02   | 18    |
| 19    | 0.04   | 1.0160  | 0.0359       | 0.912  | 19    |
| 20    | 0.036  | 0.9144  | 0.0320       | 0.813  | 20    |
| 21    | 0.032  | 0.8128  | 0.0285       | 0.724  | 21    |
| 22    | 0.028  | 0.7112  | 0.0254       | 0.645  | 22    |
| 23    | 0.024  | 0.6096  | 0.0220       | 0.559  | 23    |
| 24    | 0.022  | 0.5588  | 0.0201       | 0.511  | 24    |
| 25    | 0.020  | 0.5080  | 0.0179       | 0.455  | 25    |
| 26    | 0.018  | 0.4572  | 0.0159       | 0.404  | 26    |
| 27    | 0.0164 | 0.4166  | 0.0142       | 0.361  | 27    |
| 28    | 0.0149 | 0.3785  | 0.0126       | 0.320  | 28    |
| 29    | 0.0136 | 0.3454  | 0.0113       | 0.287  | 29    |
| 30    | 0.0124 | 0.3150  | 0.0100       | 0.254  | 30    |
| 31    | 0.0116 | 0.2946  | 0.00893      | 0.227  | 31    |
| 32    | 0.0108 | 0.2743  | 0.00795      | 0.202  | 32    |
| 33    | 0.0100 | 0.2540  | 0.00708      | 0.180  | 33    |
| 34    | 0.0092 | 0.2337  | 0.00632      | 0.161  | 34    |
| 35    | 0.0084 | 0.2134  | 0.00562      | 0.143  | 35    |
| 36    | 0.0076 | 0.1930  | 0.00500      | 0.127  | 36    |
| 37    | 0.0068 | 0.1727  | 0.00445      | 0.113  | 37    |
| 38    | 0.0060 | 0.1524  | 0.00397      | 0.101  | 38    |
| 39    | 0.0052 | 0.1321  | 0.00353      | 0.0897 | 39    |
| 40    | 0.0048 | 0.1219  | 0.00315      | 0.0800 | 40    |
| 41    | 0.0044 | 0.1118  | 0.00280      | 0.0711 | 41    |
| 42    | 0.0040 | 0.1016  | 0.00249      | 0.0632 | 42    |
| 43    | 0.0036 | 0.0914  | 0.00222      | 0.0564 | 43    |
| 44    | 0.0032 | 0.0813  | 0.00198      | 0.0503 | 44    |
| 45    | 0.0028 | 0.0711  | 0.00176      | 0.0447 | 45    |
| 46    | 0.0024 | 0.0610  | 0.00157      | 0.0399 | 46    |
| 47    | 0.0020 | 0.0508  | 0.00140      | 0.0356 | 47    |
| 48    | 0.0016 | 0.0406  | 0.00124      | 0.0315 | 48    |
| 49    | 0.0012 | 0.0305  | 0.00111      | 0.0282 | 49    |
| 50    | 0.0010 | 0.0254  | 0.00099      | 0.0251 | 50    |

### Conversion °Centigrade / °Fahrenheit

| °C     | °F | °C    | °F   | °C  | °F    | °C  | °F  |      |      |      |      |
|--------|----|-------|------|-----|-------|-----|-----|------|------|------|------|
| -17.80 | 0  | 32.0  | 10.0 | 50  | 122.0 | 38  | 100 | 212  | 310  | 590  | 1094 |
| -17.20 | 1  | 33.8  | 10.6 | 51  | 123.8 | 43  | 110 | 230  | 316  | 600  | 1112 |
| -16.70 | 2  | 35.6  | 11.1 | 52  | 125.6 | 49  | 120 | 248  | 321  | 610  | 1130 |
| -16.10 | 3  | 37.4  | 11.7 | 53  | 127.4 | 54  | 130 | 266  | 327  | 620  | 1148 |
| -15.56 | 4  | 39.2  | 12.2 | 54  | 129.2 | 60  | 140 | 284  | 332  | 630  | 1166 |
| -15.00 | 5  | 41.0  | 12.8 | 55  | 131.0 | 66  | 150 | 302  | 338  | 640  | 1184 |
| -14.44 | 6  | 42.8  | 13.3 | 56  | 132.8 | 71  | 160 | 320  | 343  | 650  | 1202 |
| -13.89 | 7  | 44.6  | 13.9 | 57  | 134.6 | 77  | 170 | 338  | 349  | 660  | 1220 |
| -13.33 | 8  | 46.4  | 14.4 | 58  | 136.4 | 82  | 180 | 356  | 354  | 670  | 1238 |
| -12.78 | 9  | 48.2  | 15.0 | 59  | 138.2 | 88  | 190 | 374  | 360  | 680  | 1256 |
| -12.22 | 10 | 50.0  | 15.6 | 60  | 140.0 | 93  | 200 | 392  | 366  | 690  | 1274 |
| -11.67 | 11 | 51.8  | 16.1 | 61  | 141.8 | 99  | 210 | 410  | 371  | 700  | 1292 |
| -11.11 | 12 | 53.6  | 16.7 | 62  | 143.6 | 100 | 212 | 413  | 377  | 710  | 1310 |
| -10.56 | 13 | 55.4  | 17.2 | 63  | 145.4 | 104 | 220 | 428  | 382  | 720  | 1328 |
| -10.00 | 14 | 57.2  | 17.8 | 64  | 147.2 | 110 | 230 | 446  | 388  | 730  | 1346 |
| -9.44  | 15 | 59.0  | 18.3 | 65  | 149.0 | 116 | 240 | 464  | 393  | 740  | 1364 |
| -8.89  | 16 | 60.8  | 18.9 | 66  | 150.8 | 121 | 250 | 482  | 399  | 750  | 1382 |
| -8.33  | 17 | 62.6  | 19.4 | 67  | 152.6 | 127 | 260 | 500  | 404  | 760  | 1400 |
| -7.78  | 18 | 64.4  | 20.0 | 68  | 154.4 | 132 | 270 | 518  | 410  | 770  | 1418 |
| -7.22  | 19 | 66.2  | 20.6 | 69  | 156.2 | 138 | 280 | 536  | 416  | 780  | 1436 |
| -6.67  | 20 | 68.0  | 21.1 | 70  | 158.0 | 143 | 290 | 554  | 421  | 790  | 1454 |
| -6.11  | 21 | 69.8  | 21.7 | 71  | 159.8 | 149 | 300 | 572  | 427  | 800  | 1472 |
| -5.56  | 22 | 71.6  | 22.2 | 72  | 161.6 | 154 | 310 | 590  | 432  | 810  | 1490 |
| -5.00  | 23 | 73.4  | 22.8 | 73  | 163.4 | 160 | 320 | 608  | 438  | 820  | 1508 |
| -4.44  | 24 | 75.2  | 23.3 | 74  | 165.2 | 166 | 330 | 626  | 443  | 830  | 1526 |
| -3.89  | 25 | 77.0  | 23.9 | 75  | 167.0 | 171 | 340 | 644  | 449  | 840  | 1544 |
| -3.33  | 26 | 78.8  | 24.4 | 76  | 168.8 | 177 | 350 | 662  | 454  | 850  | 1562 |
| -2.78  | 27 | 80.6  | 25.0 | 77  | 170.6 | 182 | 360 | 680  | 460  | 860  | 1580 |
| -2.22  | 28 | 82.4  | 25.6 | 78  | 172.4 | 188 | 370 | 698  | 466  | 870  | 1598 |
| -1.67  | 29 | 84.2  | 26.1 | 79  | 174.2 | 193 | 380 | 716  | 471  | 880  | 1616 |
| -1.11  | 30 | 86.0  | 26.7 | 80  | 176.0 | 199 | 390 | 734  | 477  | 890  | 1634 |
| -0.56  | 31 | 87.8  | 27.2 | 81  | 177.8 | 204 | 400 | 752  | 482  | 900  | 1652 |
| 0.00   | 32 | 89.6  | 27.8 | 82  | 179.6 | 210 | 410 | 770  | 488  | 910  | 1670 |
| 0.56   | 33 | 91.4  | 28.3 | 83  | 181.4 | 216 | 420 | 788  | 493  | 920  | 1688 |
| 1.11   | 34 | 93.2  | 28.9 | 84  | 183.2 | 221 | 430 | 806  | 499  | 930  | 1706 |
| 1.67   | 35 | 95.0  | 29.4 | 85  | 185.0 | 227 | 440 | 824  | 504  | 940  | 1724 |
| 2.22   | 36 | 96.8  | 30.0 | 86  | 186.8 | 232 | 450 | 842  | 510  | 950  | 1742 |
| 2.78   | 37 | 98.6  | 30.6 | 87  | 188.6 | 238 | 460 | 860  | 516  | 960  | 1760 |
| 3.33   | 38 | 100.4 | 31.1 | 88  | 190.4 | 243 | 470 | 878  | 521  | 970  | 1778 |
| 3.89   | 39 | 102.2 | 31.7 | 89  | 192.2 | 249 | 480 | 896  | 527  | 980  | 1796 |
| 4.44   | 40 | 104.0 | 32.2 | 90  | 194.0 | 254 | 490 | 914  | 532  | 990  | 1814 |
| 5.00   | 41 | 105.8 | 32.8 | 91  | 195.8 | 260 | 500 | 932  | 538  | 1000 | 1832 |
| 5.56   | 42 | 107.6 | 33.3 | 92  | 197.6 | 266 | 510 | 950  | 593  | 1100 | 2012 |
| 6.11   | 43 | 109.4 | 33.9 | 93  | 199.4 | 271 | 520 | 968  | 649  | 1200 | 2192 |
| 6.67   | 44 | 111.2 | 34.4 | 94  | 201.2 | 277 | 530 | 986  | 704  | 1300 | 2372 |
| 7.22   | 45 | 113.0 | 35.0 | 95  | 203.0 | 282 | 540 | 1004 | 760  | 1400 | 2552 |
| 7.78   | 46 | 114.8 | 35.6 | 96  | 204.8 | 288 | 550 | 1022 | 816  | 1500 | 2732 |
| 8.33   | 47 | 116.6 | 36.1 | 97  | 206.6 | 293 | 560 | 1040 | 871  | 1600 | 2912 |
| 8.89   | 48 | 118.4 | 36.7 | 98  | 208.4 | 299 | 570 | 1058 | 927  | 1700 | 3092 |
| 9.44   | 49 | 120.2 | 37.2 | 99  | 210.2 | 304 | 580 | 1076 | 982  | 1800 | 3272 |
|        |    |       | 37.8 | 100 | 212.0 |     |     |      | 1000 | 1832 | 3330 |

**Example:** 50 °C = 122 °F; 50 °F = 10 °C

**Calculation:** °F = 9/5 °C + 32; °C = 5/9 (°F - 32)

# Quality

At ISABELLENHÜTTE, the quality of our products forms the basis of your business success and ours. Meeting all quality requirements and thus quality assurance through constant improvement of procedures, processes and operating steps is the personal objective of our staff. Internal and external training ensures that all employees are highly qualified.

ISABELLENHÜTTE's knowledge and technical expertise in the field of electro-physics together with significant investment in the research and development of advanced manufacturing processes makes our products the ideal Solution to your Problems.

Our company has adopted a quality management system in accordance with the requirements of ISO/TS 16949 and is certificated by the DQS GmbH – Deutsche Gesellschaft zur Zertifizierung von Managementsystemen.

EMF measurements are in accordance with ASTM E 207. Wire standards are calibrated in our own DKD calibration laboratory (registration number: DKD-K-03101).

ISABELLENHÜTTE's long term experience of packing our products in accordance with highest standards ensures receipt in perfect condition at our business partners.

**It's our tradition:  
QUALITY – let's prove it to you!**

We look forward to establishing a close technical and business relationship.

**Commercial:**

Phone: +49 (27 71) 9 34-1 40 / -1 42  
 Fax: +49 (27 71) 2 30 30  
 E-Mail: vk.export@isabellenhuette.de

**Technical:**

Phone: +49 (27 71) 9 34-2 50  
 Fax: +49 (27 71) 2 30 30  
 E-Mail: thermo@isabellenhuette.de

